



Model: SEAGATE ST9146853SS
S/N: 6XM26D86



Disk Erasure Report

Page 1 - Erasure Status

Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-0**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE ST9146853SS**

Serial: **6XM26D86**

Size(Apparent): **146 GB, 146815733760 bytes**

Bus: **SAS**

Size(Real): **146 GB, 146815733760 bytes**

Disk Erasure Details

Start time: **2025/02/05 06:11:37**

End time: **2025/02/05 06:11:46**

Duration: **00:00:09**

Status: **ABORTED**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **1228795904, (0.83%)**

Rounds(completed/requested): **0/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **203 MB/sec**

Information: **Warning** HPA/DCO data unavailable, can not determine hidden sector status.

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST9146853SS
S/N: 6XM26D86



Disk Erasure Report

Page 2 - Smart Data

smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.11.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE
product: ST9146853SS
revision: YS09
compliance: SPC-4
user capacity: 146,815,733,760 bytes [146 GB]
logical block size: 512 bytes
rotation rate: 15000 rpm
form factor: 2.5 inches
logical unit id: 0x5000c5005f30a7b3
serial number: 6XM26D86
device type: disk
transport protocol: SAS (SPL-3)
local time is: Wed Feb 5 06:11:46 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 30 C
drive trip temperature: 68 C

accumulated power on time, hours:minutes 67170:19
manufactured in week 04 of year 2013
specified cycle count over device lifetime: 10000
accumulated start-stop cycles: 26
elements in grown defect list: 613

vendor (seagate cache) information

blocks sent to initiator = 372258067
blocks received from initiator = 2521029003
blocks read from cache and sent to initiator = 47678134
number of read and write commands whose size <= segment size = 991246712
number of read and write commands whose size > segment size = 37

vendor (seagate/hitachi) factory information

number of hours powered up = 67170.32
number of minutes until next internal smart test = 17

error counter log:

	errors corrected by	total	correction	gigabytes	total		
	ecc	errors	algorithm	processed	uncorrected		
	fast delayed	rereads/ rewrites	corrected	invocations	[10^9 bytes]	errors	
read:	2912093824	0	0	2912093824	0	598.787	0
write:	0	0	0	3	136254.675	2	
verify:	3968764487	227	0	3968764714	228	66769.393	1

non-medium error count: 107

smart self-test log

num	test	status	segment	lifetime	lba_first_err	[sk asc asq]
	description		number	(hours)		
# 1	background short	completed	32	2	-	[- - -]
# 2	background long	completed	32	1	-	[- - -]
# 3	background short	completed	32	1	-	[- - -]

long (extended) self-test duration: 1099 seconds [18.3 minutes]