



Model: Samsung SSD 850

S/N: S21DNXAH103908V



Disk Erasure Report

Page 1 - Erasure Status

Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-6**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **Samsung SSD 850**

Serial: **S21DNXAH103908V**

Size(Apparent): **1000 GB, 1000204886016 bytes**

Bus: **ATA-SSD**

Size(Real): **1000 GB, 1000204886016 bytes**

Disk Erasure Details

Start time: **2025/02/10 16:17:25**

End time: **2025/02/10 18:41:58**

Duration: **02:24:33**

Status: **ERASED**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **1000204886016, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **No hidden sectors**

HPA/DCO Size: **No hidden sectors**

Errors(pass/sync/verify): **0/0/0**

Throughput: **345 MB/sec**


Information:

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: Samsung SSD 850
S/N: S21DNXAH103908V



Disk Erasure Report

Page 2 - Smart Data

smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

```
=== start of information section ===
model family:      Samsung based SSDs
device model:      Samsung SSD 850 EVO 1TB
serial number:     S21DNXAH103908V
lu wwn device id:  5 002538 840154256
firmware version:  EMT02B6Q
user capacity:     1,000,204,886,016 bytes [1.00 TB]
sector size:       512 bytes logical/physical
rotation rate:     Solid State Device
form factor:       2.5 inches
trim command:      Available
device is:         In smartctl database [for details use: -P show]
ata version is:    ACS-2, ATA8-ACS T13/1699-D revision 4c
sata version is:   SATA 3.1, 6.0 Gb/s (current: 6.0 Gb/s)
local time is:     Mon Feb 10 18:42:47 2025 GMT
smart support is:  Available - device has SMART capability.
smart support is:  Enabled
```

```
=== start of read smart data section ===
smart overall-health self-assessment test result: PASSED
```

```
general smart values:
offline data collection status: (0x00)Offline data collection activity
was never started.
auto offline data collection: Disabled.
self-test execution status:      ( 0)The previous self-test routine completed
without error or no self-test has ever
been run.
total time to complete offline
data collection: ( 0) seconds.
offline data collection
capabilities: (0x53) SMART execute Offline immediate.
auto offline data collection on/off support.
suspend offline collection upon new
command.
no offline surface scan supported.
self-test supported.
no conveyance self-test supported.
selective self-test supported.
smart capabilities: (0x0003)Saves SMART data before entering
power-saving mode.
supports smart auto save timer.
error logging capability: (0x01)Error logging supported.
general purpose logging supported.
short self-test routine
recommended polling time: ( 2) minutes.
extended self-test routine
recommended polling time: ( 530) minutes.
sct capabilities: (0x003d)SCT Status supported.
sct error recovery control supported.
sct feature control supported.
sct data table supported.
```

```
smart attributes data structure revision number: 1
vendor specific smart attributes with thresholds:
```

id#	attribute_name	flag	value	worst	thresh	type	updated	when_failed	raw_value
5	reallocated_sector_ct	0x0033	054	054	010	pre-fail	always	-	1819
9	power_on_hours	0x0032	081	081	000	old_age	always	-	93837
12	power_cycle_count	0x0032	099	099	000	old_age	always	-	43
177	wear_leveling_count	0x0013	004	004	000	pre-fail	always	-	1937
179	used_rsvid_blk_cnt_tot	0x0013	054	054	010	pre-fail	always	-	1819



Model: Samsung SSD 850

S/N: S21DNXAH103908V



Disk Erasure Report

Page 3 - Smart Data

181	program_fail_cnt_total	0x0032	100	100	010	old_age	always	-	0
182	erase_fail_count_total	0x0032	054	054	010	old_age	always	-	1819
183	runtime_bad_block	0x0013	054	054	010	pre-fail	always	-	1819
187	uncorrectable_error_cnt	0x0032	100	100	000	old_age	always	-	0
190	airflow_temperature_cel	0x0032	064	055	000	old_age	always	-	36
195	ecc_error_rate	0x001a	200	200	000	old_age	always	-	0
199	crc_error_count	0x003e	099	099	000	old_age	always	-	2
235	por_recovery_count	0x0012	099	099	000	old_age	always	-	33
241	total_lbas_written	0x0032	098	098	000	old_age	always	-	3152865504288

smart error log version: 1
no errors logged

smart self-test log structure revision number 1
no self-tests have been logged. [to run self-tests, use: smartctl -t]

smart selective self-test log data structure revision number 1

span	min_lba	max_lba	current_test_status
------	---------	---------	---------------------

1	0	0	not_testing
2	0	0	not_testing
3	0	0	not_testing
4	0	0	not_testing
5	0	0	not_testing

selective self-test flags (0x0):

after scanning selected spans, do not read-scan remainder of disk.
if selective self-test is pending on power-up, resume after 0 minute delay.