



Model: SEAGATE ST300MM0006

S/N: S0K1MB6G

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-0**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE ST300MM0006**

Serial: **S0K1MB6G**

Size(Apparent): **300 GB, 300000000000 bytes**

Bus: **SAS**

Size(Real): **300 GB, 300000000000 bytes**

Disk Erasure Details

Start time: **2025/02/12 12:12:31**

End time: **2025/02/12 13:53:17**

Duration: **01:40:46**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **300000000000, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **148 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST300MM0006

S/N: S0K1MB6G

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.22.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE
product: ST300MM0006
revision: LS0C
compliance: SPC-4
user capacity: 300,000,000,000 bytes [300 GB]
logical block size: 512 bytes
lu is fully provisioned
rotation rate: 10000 rpm
form factor: 2.5 inches
logical unit id: 0x5000c50070ef0153
serial number: S0K1MB6G
device type: disk
transport protocol: SAS (SPL-3)
local time is: Wed Feb 12 13:53:19 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 30 C
drive trip temperature: 60 C

accumulated power on time, hours:minutes 6629:34
manufactured in week 49 of year 2013
specified cycle count over device lifetime: 10000
accumulated start-stop cycles: 123
specified load-unload count over device lifetime: 300000
accumulated load-unload cycles: 5483
elements in grown defect list: 0

vendor (seagate cache) information

blocks sent to initiator = 1888770111
blocks received from initiator = 1845763987
blocks read from cache and sent to initiator = 1290490613
number of read and write commands whose size <= segment size = 503426045
number of read and write commands whose size > segment size = 38

vendor (seagate/hitachi) factory information

number of hours powered up = 6629.57
number of minutes until next internal smart test = 19

error counter log:

	errors corrected by			total	correction	gigabytes	total
	ecc	rereads/		errors	algorithm	processed	uncorrected
	fast delayed	rewrites		corrected	invocations	[10^9 bytes]	errors
read:	1352652444	0	0	1352652444	0	18535.892	0
write:	0	0	3	3	3	146078.511	0
verify:	125629017	0	0	125629017	0	129469.364	0

non-medium error count: 37

smart self-test log

num	test	status	segment	lifetime	lba_first_err	[sk asc asq]
	description		number	(hours)		
# 1	background short	completed	48	3	-	[- - -]
# 2	reserved(7)	completed	32	3	-	[- - -]
# 3	background short	completed	48	1	-	[- - -]



Model: SEAGATE ST300MM0006
S/N: S0K1MB6G

Disk Erasure Report

Page 3 - Smart Data



long (extended) self-test duration: 1905 seconds [31.8 minutes]