



Model: SEAGATE ST3300656SS
S/N: 3QP2XZYB



Disk Erasure Report

Page 1 - Erasure Status

Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-2**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE ST3300656SS**

Serial: **3QP2XZYB**

Size(Apparent): **300 GB, 300000000000 bytes**

Bus: **SAS**

Size(Real): **300 GB, 300000000000 bytes**

Disk Erasure Details

Start time: **2025/02/12 12:09:27**

End time: **2025/02/12 14:09:58**

Duration: **02:00:31**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **300000000000, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **124 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST3300656SS
S/N: 3QP2XZYB



Disk Erasure Report

Page 2 - Smart Data

smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE
product: ST3300656SS
revision: HS0F
compliance: SPC-3
user capacity: 300,000,000,000 bytes [300 GB]
logical block size: 512 bytes
rotation rate: 15000 rpm
logical unit id: 0x5000c5001cd2940f
serial number: 3QP2XZYB
device type: disk
transport protocol: SAS (SPL-3)
local time is: Wed Feb 12 14:09:59 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 33 C
drive trip temperature: 68 C

accumulated power on time, hours:minutes 46447:42
elements in grown defect list: 1

vendor (seagate cache) information

blocks sent to initiator = 3793175251
blocks received from initiator = 1747232600
blocks read from cache and sent to initiator = 2654143443
number of read and write commands whose size <= segment size = 1160097929
number of read and write commands whose size > segment size = 2075039

vendor (seagate/hitachi) factory information

number of hours powered up = 46447.70
number of minutes until next internal smart test = 59

error counter log:

	errors corrected by ecc	rereads/ rewrites	total errors corrected	correction algorithm invocations	gigabytes processed [10 ⁹ bytes]	total uncorrected errors
read:	134102850	0	134102850	134102850	142782.213	0
write:	0	0	0	1	9861.387	1
verify:	12875965	0	12875965	12875965	21879.024	0

non-medium error count: 99

smart self-test log

num	test description	status	segment number	lifetime (hours)	lba_first_err	[sk asc asq]
# 1	background long	completed	16	88	-	[- - -]
# 2	background short	completed	16	88	-	[- - -]
# 3	background long	completed	16	64	-	[- - -]
# 4	background short	completed	16	63	-	[- - -]
# 5	background long	completed	16	3	-	[- - -]
# 6	background short	completed	16	2	-	[- - -]

long (extended) self-test duration: 2460 seconds [41.0 minutes]