

Model: TOSHIBA AL13SEB300

S/N: 44B0A003FRD6

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-6**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **TOSHIBA AL13SEB300**

Serial: **44B0A003FRD6**

Size(Apparent): **300 GB, 300000000000 bytes**

Bus: **SAS**

Size(Real): **300 GB, 300000000000 bytes**

Disk Erasure Details

Start time: **2025/02/12 12:15:28**

End time: **2025/02/12 14:24:26**

Duration: **02:08:58**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **300000000000, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **116 MB/sec**


Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: TOSHIBA AL13SEB300

S/N: 44B0A003FRD6

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: TOSHIBA
product: AL13SEB300
revision: DE11
compliance: SPC-4
user capacity: 300,000,000,000 bytes [300 GB]
logical block size: 512 bytes
rotation rate: 10000 rpm
form factor: 2.5 inches
logical unit id: 0x50000395780ac63c
serial number: 44B0A003FRD6
device type: disk
transport protocol: SAS (SPL-3)
local time is: Wed Feb 12 14:24:27 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 32 C
drive trip temperature: 65 C

accumulated power on time, hours:minutes 83711:19
manufactured in week 15 of year 2014
specified cycle count over device lifetime: 50000
accumulated start-stop cycles: 33
specified load-unload count over device lifetime: 200000
accumulated load-unload cycles: 9716
elements in grown defect list: 0

error counter log:

	errors corrected by		total		correction	gigabytes	total
	ecc		errors		algorithm	processed	uncorrected
	fast	delayed	rereads/ rewrites	corrected	invocations	[10 ⁹ bytes]	errors
read:	0	2	2	2	2	1551122.715	0
write:	0	66	66	66	69	150771.461	0
verify:	0	0	0	0	0	149648.161	0

non-medium error count: 26

smart self-test log

num	test description	status	segment number	lifetime (hours)	lba_first_err	[sk asc asq]
# 1	background short	completed	64	2	-	[- - -]
# 2	background long	completed	64	2	-	[- - -]
# 3	background short	completed	64	2	-	[- - -]

long (extended) self-test duration: 2001 seconds [33.4 minutes]