



Model: HITACHI HUS156060VLS600

S/N: LXWAB6DJ

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-3**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **HITACHI HUS156060VLS600**

Serial: **LXWAB6DJ**

Size(Apparent): **600 GB, 600127266816 bytes**

Bus: **SAS**

Size(Real): **600 GB, 600127266816 bytes**

Disk Erasure Details

Start time: **2025/02/12 12:10:34**

End time: **2025/02/12 15:45:54**

Duration: **03:35:20**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **600127266816, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **139 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: HITACHI HUS156060VLS600

S/N: LXWAB6DJ

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: HITACHI
product: HUS156060VLS600
revision: E516
compliance: SPC-4
user capacity: 600,127,266,816 bytes [600 GB]
logical block size: 512 bytes
rotation rate: 15030 rpm
form factor: 3.5 inches
logical unit id: 0x5000cca02a4b3520
serial number: LXWAB6DJ
device type: disk
transport protocol: SAS (SPL-3)
local time is: Wed Feb 12 15:45:55 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 40 C
drive trip temperature: 85 C

accumulated power on time, hours:minutes 40202:28
manufactured in week 21 of year 2012
specified cycle count over device lifetime: 50000
accumulated start-stop cycles: 15
elements in grown defect list: 0

vendor (seagate cache) information
blocks sent to initiator = 109338792413888512

error counter log:

	errors corrected by		total		correction	gigabytes	total
	ecc		errors		algorithm	processed	uncorrected
	fast	delayed	rereads/ rewrites	corrected	invocations	[10 ⁹ bytes]	errors
read:	0	2778188	0	2778188	7619796	39169.089	0
write:	0	20868493	0	20868493	16143736	246416.625	0
verify:	0	743463	0	743463	302340	356500.513	0

non-medium error count: 2

smart self-test log

num	test	status	segment number	lifetime (hours)	lba_first_err	[sk asc asq]
# 1	background short	completed	16	7	-	[- - -]
# 2	background short	completed	16	6	-	[- - -]
# 3	background short	completed	16	6	-	[- - -]
# 4	background short	completed	16	5	-	[- - -]

long (extended) self-test duration: 4981 seconds [83.0 minutes]