



Model: TOSHIBA AL13SEB600

S/N: 54U0A02XFRD4

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-6**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **TOSHIBA AL13SEB600**

Serial: **54U0A02XFRD4**

Size(Apparent): **600 GB, 600127266816 bytes**

Bus: **SAS**

Size(Real): **600 GB, 600127266816 bytes**

Disk Erasure Details

Start time: **2025/02/12 12:14:52**

End time: **2025/02/12 16:12:01**

Duration: **03:57:09**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **600127266816, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **126 MB/sec**


Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: TOSHIBA AL13SEB600

S/N: 54U0A02XFRD4

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: TOSHIBA
product: AL13SEB600
revision: DE09
compliance: SPC-4
user capacity: 600,127,266,816 bytes [600 GB]
logical block size: 512 bytes
rotation rate: 10000 rpm
form factor: 2.5 inches
logical unit id: 0x50000395883bcfcc
serial number: 54U0A02XFRD4
device type: disk
transport protocol: SAS (SPL-3)
local time is: Wed Feb 12 16:12:03 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 34 C
drive trip temperature: 50 C

accumulated power on time, hours:minutes 88333:33
manufactured in week 22 of year 2014
specified cycle count over device lifetime: 50000
accumulated start-stop cycles: 27
specified load-unload count over device lifetime: 200000
accumulated load-unload cycles: 133
elements in grown defect list: 0

error counter log:

	errors corrected by		total	correction	gigabytes	total	
	ecc	rereads/	errors	algorithm	processed	uncorrected	
	fast	delayed	rewrites	corrected	invocations	[10 ⁹ bytes] errors	
read:	0	103	103	103	132	3237691.460	0
write:	0	808	808	808	1416	89484.175	0
verify:	0	10	10	10	10	316065.466	0

non-medium error count: 29

smart self-test log

num	test	status	segment	lifetime	lba_first_err	[sk asc asq]
	description		number	(hours)		
# 1	background short	completed	64	3	-	[- - -]
# 2	background long	completed	64	3	-	[- - -]
# 3	background short	completed	64	1	-	[- - -]

long (extended) self-test duration: 3964 seconds [66.1 minutes]