



Model: SEAGATE ST600MM0006

S/N: S0M39FX9

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-6**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE ST600MM0006**

Serial: **S0M39FX9**

Size(Apparent): **600 GB, 600127266816 bytes**

Bus: **SAS**

Size(Real): **600 GB, 600127266816 bytes**

Disk Erasure Details

Start time: **2025/02/12 14:32:58**

End time: **2025/02/12 18:28:48**

Duration: **03:55:50**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **600127266816, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **127 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST600MM0006

S/N: S0M39FX9

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE
product: ST600MM0006
revision: LS0A
compliance: SPC-4
user capacity: 600,127,266,816 bytes [600 GB]
logical block size: 512 bytes
lu is fully provisioned
rotation rate: 10000 rpm
form factor: 2.5 inches
logical unit id: 0x5000c5007734feb3
serial number: S0M39FX9
device type: disk
transport protocol: SAS (SPL-3)
local time is: Wed Feb 12 18:28:49 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 31 C
drive trip temperature: 50 C

accumulated power on time, hours:minutes 10242:29
manufactured in week 33 of year 2014
specified cycle count over device lifetime: 10000
accumulated start-stop cycles: 27
specified load-unload count over device lifetime: 300000
accumulated load-unload cycles: 3745
elements in grown defect list: 1

vendor (seagate cache) information

blocks sent to initiator = 1864603113
blocks received from initiator = 576860812
blocks read from cache and sent to initiator = 3929090404
number of read and write commands whose size <= segment size = 743345501
number of read and write commands whose size > segment size = 23

vendor (seagate/hitachi) factory information

number of hours powered up = 10242.48
number of minutes until next internal smart test = 14

error counter log:

	errors corrected by ecc	fast delayed	rereads/ rewrites	total errors corrected	correction algorithm invocations	gigabytes processed [10^9 bytes]	total uncorrected errors
read:	3914764765	0	0	3914764765	0	199092.789	0
write:	0	0	16	16	19	55346.388	2
verify:	2554298412	0	0	2554298412	0	316175.631	0

non-medium error count: 12

smart self-test log

num	test description	status	segment number	lifetime (hours)	lba_first_err	[sk asc asq]
# 1	background short	completed	64	3	-	[- - -]
# 2	reserved(7)	completed	48	3	-	[- - -]
# 3	background short	completed	64	1	-	[- - -]



Model: SEAGATE ST600MM0006

S/N: S0M39FX9

Disk Erasure Report

Page 3 - Smart Data



long (extended) self-test duration: 3777 seconds [63.0 minutes]