



Model: SEAGATE ST600MM0006

S/N: S0M391KQ

# Disk Erasure Report

Page 1 - Erasure Status



## Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-5**

Contact Phone:

## Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

## Disk Information

Make/Model: **SEAGATE ST600MM0006**

Serial: **S0M391KQ**

Size(Apparent): **600 GB, 600127266816 bytes**

Bus: **SAS**

Size(Real): **600 GB, 600127266816 bytes**

## Disk Erasure Details

Start time: **2025/02/12 14:33:15**

End time: **2025/02/12 18:32:33**

Duration: **03:59:18**

Status: **FAILED**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

\*Bytes Erased: **600127266816, (100.00%)**

Rounds(completed/requested): **0/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **1/0/5312**

Throughput: **125 MB/sec**

Information: **Warning** HPA/DCO data unavailable, can not determine hidden sector status.

\* bytes erased: The amount of drive that's been erased at least once

## Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST600MM0006

S/N: S0M391KQ

# Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86\_64-linux-5.14.0-503.23.1.el9\_5.x86\_64] (local build)  
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE  
product: ST600MM0006  
revision: LS0A  
compliance: SPC-4  
user capacity: 600,127,266,816 bytes [600 GB]  
logical block size: 512 bytes  
lu is fully provisioned  
rotation rate: 10000 rpm  
form factor: 2.5 inches  
logical unit id: 0x5000c5007734e713  
serial number: S0M391KQ  
device type: disk  
transport protocol: SAS (SPL-3)  
local time is: Wed Feb 12 18:32:35 2025 GMT  
smart support is: Available - device has SMART capability.  
smart support is: Enabled  
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 36 C  
drive trip temperature: 50 C

accumulated power on time, hours:minutes 10242:59  
manufactured in week 33 of year 2014  
specified cycle count over device lifetime: 10000  
accumulated start-stop cycles: 27  
specified load-unload count over device lifetime: 300000  
accumulated load-unload cycles: 3751  
elements in grown defect list: 2

vendor (seagate cache) information

blocks sent to initiator = 4074729184  
blocks received from initiator = 4087549434  
blocks read from cache and sent to initiator = 4123789804  
number of read and write commands whose size <= segment size = 726093302  
number of read and write commands whose size > segment size = 24

vendor (seagate/hitachi) factory information

number of hours powered up = 10242.98  
number of minutes until next internal smart test = 10


error counter log:

	errors corrected by		total	correction	gigabytes	total	
	ecc	rereads/	errors	algorithm	processed	uncorrected	
	fast   delayed	rewrites	corrected	invocations	[10^9 bytes]	errors	
read:	2782332900	0	0	2782332900	0	200483.787	1
write:	0	0	2340	2340	2342	46621.833	3
verify:	2189647609	0	0	2189647609	0	316165.327	0

non-medium error count: 29

smart self-test log

num	test	status	segment	lifetime	lba_first_err	[sk asc asq]
	description		number	(hours)		
# 1	background short	completed	64	3	-	[- - -]
# 2	reserved(7)	completed	48	3	-	[- - -]
# 3	background short	completed	64	1	-	[- - -]



Model: SEAGATE ST600MM0006  
S/N: S0M391KQ

# Disk Erasure Report

Page 3 - Smart Data



---

long (extended) self-test duration: 3777 seconds [63.0 minutes]