

Model: SEAGATE ST600MM0006

S/N: S0M39FYP

# Disk Erasure Report

Page 1 - Erasure Status



## Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-5**

Contact Phone:

## Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

## Disk Information

Make/Model: **SEAGATE ST600MM0006**

Serial: **S0M39FYP**

Size(Apparent): **600 GB, 600127266816 bytes**

Bus: **SAS**

Size(Real): **600 GB, 600127266816 bytes**

## Disk Erasure Details

Start time: **2025/02/12 14:33:11**

End time: **2025/02/12 18:35:13**

Duration: **04:02:02**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

\*Bytes Erased: **600127266816, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **123 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

\* bytes erased: The amount of drive that's been erased at least once

## Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST600MM0006

S/N: S0M39FYP

# Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86\_64-linux-5.14.0-503.23.1.el9\_5.x86\_64] (local build)  
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE  
product: ST600MM0006  
revision: LS0A  
compliance: SPC-4  
user capacity: 600,127,266,816 bytes [600 GB]  
logical block size: 512 bytes  
lu is fully provisioned  
rotation rate: 10000 rpm  
form factor: 2.5 inches  
logical unit id: 0x5000c5007734fd4f  
serial number: S0M39FYP  
device type: disk  
transport protocol: SAS (SPL-3)  
local time is: Wed Feb 12 18:35:14 2025 GMT  
smart support is: Available - device has SMART capability.  
smart support is: Enabled  
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 36 C  
drive trip temperature: 50 C

accumulated power on time, hours:minutes 10243:27  
manufactured in week 33 of year 2014  
specified cycle count over device lifetime: 10000  
accumulated start-stop cycles: 27  
specified load-unload count over device lifetime: 300000  
accumulated load-unload cycles: 3749  
elements in grown defect list: 1

vendor (seagate cache) information

blocks sent to initiator = 3838187458  
blocks received from initiator = 1369259540  
blocks read from cache and sent to initiator = 3994023693  
number of read and write commands whose size <= segment size = 744926247  
number of read and write commands whose size > segment size = 23

vendor (seagate/hitachi) factory information

number of hours powered up = 10243.45  
number of minutes until next internal smart test = 59


error counter log:

|         | errors corrected by | total                | correction               | gigabytes    | total       |   |
|---------|---------------------|----------------------|--------------------------|--------------|-------------|---|
|         | ecc                 | errors               | algorithm                | processed    | uncorrected |   |
|         | fast   delayed      | rereads/<br>rewrites | corrected<br>invocations | [10^9 bytes] | errors      |   |
| read:   | 1243831181          | 0                    | 1243831181               | 0            | 195586.015  | 0 |
| write:  | 0                   | 0                    | 5452                     | 5454         | 47853.021   | 1 |
| verify: | 2548673647          | 0                    | 2548673647               | 0            | 316191.755  | 0 |

non-medium error count: 21

smart self-test log

| num | test<br>description | status    | segment<br>number | lifetime<br>(hours) | lba_first_err | [sk asc asq] |
|-----|---------------------|-----------|-------------------|---------------------|---------------|--------------|
| # 1 | background short    | completed | 64                | 3                   | -             | [- - -]      |
| # 2 | reserved(7)         | completed | 48                | 3                   | -             | [- - -]      |
| # 3 | background short    | completed | 64                | 1                   | -             | [- - -]      |



Model: SEAGATE ST600MM0006  
S/N: S0M39FYP

# Disk Erasure Report

Page 3 - Smart Data



---

long (extended) self-test duration: 3777 seconds [63.0 minutes]