



Model: SEAGATE ST600MM0006

S/N: S0M2X3AS

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-5**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE ST600MM0006**

Serial: **S0M2X3AS**

Size(Apparent): **600 GB, 600127266816 bytes**

Bus: **SAS**

Size(Real): **600 GB, 600127266816 bytes**

Disk Erasure Details

Start time: **2025/02/12 14:33:33**

End time: **2025/02/12 18:37:58**

Duration: **04:04:25**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **600127266816, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **122 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST600MM0006

S/N: S0M2X3AS

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE
product: ST600MM0006
revision: LS0A
compliance: SPC-4
user capacity: 600,127,266,816 bytes [600 GB]
logical block size: 512 bytes
lu is fully provisioned
rotation rate: 10000 rpm
form factor: 2.5 inches
logical unit id: 0x5000c500765c1b1b
serial number: S0M2X3AS
device type: disk
transport protocol: SAS (SPL-3)
local time is: Wed Feb 12 18:38:00 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 36 C
drive trip temperature: 50 C

accumulated power on time, hours:minutes 10243:27
manufactured in week 33 of year 2014
specified cycle count over device lifetime: 10000
accumulated start-stop cycles: 27
specified load-unload count over device lifetime: 300000
accumulated load-unload cycles: 3769
elements in grown defect list: 1

vendor (seagate cache) information

blocks sent to initiator = 1828416220
blocks received from initiator = 3532912903
blocks read from cache and sent to initiator = 3616177866
number of read and write commands whose size <= segment size = 733028058
number of read and write commands whose size > segment size = 32

vendor (seagate/hitachi) factory information

number of hours powered up = 10243.45
number of minutes until next internal smart test = 59

error counter log:

	errors corrected by	total	correction	gigabytes	total
	ecc	errors	algorithm	processed	uncorrected
	fast delayed	rereads/ rewrites	corrected invocations	[10^9 bytes]	errors
read:	4091083440	0	4091083440	192729.617	0
write:	0	15797	15797	41625.156	1
verify:	1994960405	0	1994960405	316172.315	0

non-medium error count: 96

smart self-test log

num	test description	status	segment number	lifetime (hours)	lba_first_err	[sk asc asq]
# 1	background short	completed	64	3	-	[- - -]
# 2	reserved(7)	completed	48	3	-	[- - -]
# 3	background short	completed	64	1	-	[- - -]



Model: SEAGATE ST600MM0006
S/N: S0M2X3AS

Disk Erasure Report

Page 3 - Smart Data



long (extended) self-test duration: 3777 seconds [63.0 minutes]