



Model: SEAGATE ST2000NM0023

S/N: Z1X3FL7B

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-3**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE ST2000NM0023**

Serial: **Z1X3FL7B**

Size(Apparent): **2000 GB, 2000398934016 bytes**

Bus: **SAS**

Size(Real): **2000 GB, 2000398934016 bytes**

Disk Erasure Details

Start time: **2025/02/12 12:10:57**

End time: **2025/02/13 00:27:54**

Duration: **12:16:57**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **2000398934016, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **135 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST2000NM0023

S/N: Z1X3FL7B

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE
product: ST2000NM0023
revision: GS0F
compliance: SPC-4
user capacity: 2,000,398,934,016 bytes [2.00 TB]
logical block size: 512 bytes
lu is fully provisioned
rotation rate: 7200 rpm
form factor: 3.5 inches
logical unit id: 0x5000c50062a8b1a7
serial number: Z1X3FL7B
device type: disk
transport protocol: SAS (SPL-3)
local time is: Thu Feb 13 00:27:55 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 31 C
drive trip temperature: 60 C

accumulated power on time, hours:minutes 9192:04
manufactured in week 42 of year 2014
specified cycle count over device lifetime: 10000
accumulated start-stop cycles: 103
specified load-unload count over device lifetime: 300000
accumulated load-unload cycles: 4095
elements in grown defect list: 0

vendor (seagate cache) information

blocks sent to initiator = 1809299663
blocks received from initiator = 2767947546
blocks read from cache and sent to initiator = 2094643219
number of read and write commands whose size <= segment size = 204270631
number of read and write commands whose size > segment size = 18

vendor (seagate/hitachi) factory information

number of hours powered up = 9192.07
number of minutes until next internal smart test = 9

error counter log:

	errors corrected by		total	correction	gigabytes	total	
	ecc	rereads/	errors	algorithm	processed	uncorrected	
	fast delayed	rewrites	corrected	invocations	[10^9 bytes]	errors	
read:	1811529488	2	0	1811529490	2	63918.203	0
write:	0	0	30	30	71968.433	0	0
verify:	1523524516	0	0	1523524516	0	1037992.960	0

non-medium error count: 18

smart self-test log

num	test	status	segment	lifetime	lba_first_err	[sk asc asq]
	description		number	(hours)		
# 1	background short	completed	64	3	-	[- - -]
# 2	reserved(7)	completed	48	3	-	[- - -]
# 3	background short	completed	64	1	-	[- - -]



Model: SEAGATE ST2000NM0023
S/N: Z1X3FL7B

Disk Erasure Report

Page 3 - Smart Data



long (extended) self-test duration: 18300 seconds [305.0 minutes]