



Model: SEAGATE ST2000NM0023

S/N: Z1X3FN2S

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-3**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE ST2000NM0023**

Serial: **Z1X3FN2S**

Size(Apparent): **2000 GB, 2000398934016 bytes**

Bus: **SAS**

Size(Real): **2000 GB, 2000398934016 bytes**

Disk Erasure Details

Start time: **2025/02/12 12:10:32**

End time: **2025/02/13 00:37:02**

Duration: **12:26:30**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **2000398934016, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **133 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST2000NM0023

S/N: Z1X3FN2S

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE
product: ST2000NM0023
revision: GS0F
compliance: SPC-4
user capacity: 2,000,398,934,016 bytes [2.00 TB]
logical block size: 512 bytes
lu is fully provisioned
rotation rate: 7200 rpm
form factor: 3.5 inches
logical unit id: 0x5000c50062a839d7
serial number: Z1X3FN2S
device type: disk
transport protocol: SAS (SPL-3)
local time is: Thu Feb 13 00:37:03 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 33 C
drive trip temperature: 60 C

accumulated power on time, hours:minutes 9192:16
manufactured in week 42 of year 2014
specified cycle count over device lifetime: 10000
accumulated start-stop cycles: 103
specified load-unload count over device lifetime: 300000
accumulated load-unload cycles: 4081
elements in grown defect list: 0

vendor (seagate cache) information

blocks sent to initiator = 2398391166
blocks received from initiator = 3094756758
blocks read from cache and sent to initiator = 2088271156
number of read and write commands whose size <= segment size = 204436954
number of read and write commands whose size > segment size = 42

vendor (seagate/hitachi) factory information

number of hours powered up = 9192.27
number of minutes until next internal smart test = 0

error counter log:

	errors corrected by	total	correction	gigabytes	total
	ecc	errors	algorithm	processed	uncorrected
	fast delayed	rereads/ rewrites	corrected invocations	[10^9 bytes]	errors
read:	385398265 101	0	385398366 101	64390.713	0
write:	0 0	55	55	72238.369	0
verify:	882351697 4	0	882351701 4	1038023.928	0

non-medium error count: 22

smart self-test log

num	test description	status	segment number	lifetime (hours)	lba_first_err	[sk asc asq]
# 1	background short	completed	64	3	-	[- - -]
# 2	reserved(7)	completed	48	3	-	[- - -]
# 3	background short	completed	64	1	-	[- - -]



Model: SEAGATE ST2000NM0023
S/N: Z1X3FN2S

Disk Erasure Report

Page 3 - Smart Data



long (extended) self-test duration: 18300 seconds [305.0 minutes]