

Model: HGST HUC156060CSS204

S/N: 0XK9VBEP

# Disk Erasure Report

Page 1 - Erasure Status



## Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-5**

Contact Phone:

## Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

## Disk Information

Make/Model: **HGST HUC156060CSS204**

Serial: **0XK9VBEP**

Size(Apparent): **600 GB, 600127266816 bytes**

Bus: **SAS**

Size(Real): **600 GB, 600127266816 bytes**

## Disk Erasure Details

Start time: **2025/02/12 22:22:04**

End time: **2025/02/13 01:25:14**

Duration: **03:03:10**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

\*Bytes Erased: **600127266816, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **163 MB/sec**


Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

\* bytes erased: The amount of drive that's been erased at least once

## Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: HGST HUC156060CSS204

S/N: 0XK9VBEP

# Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86\_64-linux-5.14.0-503.23.1.el9\_5.x86\_64] (local build)  
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: HGST  
product: HUC156060CSS204  
revision: EJ45  
compliance: SPC-4  
user capacity: 600,127,266,816 bytes [600 GB]  
logical block size: 512 bytes  
formatted with type 2 protection  
8 bytes of protection information per logical block  
lu is fully provisioned  
rotation rate: 15000 rpm  
form factor: 2.5 inches  
logical unit id: 0x5000cca059bb0358  
serial number: 0XK9VBEP  
device type: disk  
transport protocol: SAS (SPL-3)  
local time is: Thu Feb 13 01:25:16 2025 GMT  
smart support is: Available - device has SMART capability.  
smart support is: Enabled  
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 47 C  
drive trip temperature: 50 C

accumulated power on time, hours:minutes 7721:23  
manufactured in week 50 of year 2016  
specified cycle count over device lifetime: 50000  
accumulated start-stop cycles: 30  
specified load-unload count over device lifetime: 600000  
accumulated load-unload cycles: 2838  
elements in grown defect list: 6

vendor (seagate cache) information  
blocks sent to initiator = 7220191071043584

error counter log:

	errors corrected by			total	correction	gigabytes	total
	ecc		rereads/	errors	algorithm	processed	uncorrected
	fast	delayed	rewrites	corrected	invocations	[10^9 bytes]	errors
read:	0	0	0	0	77133	2207.027	0
write:	0	2	0	4	685038	13251.386	2
verify:	0	1	0	1	169222	160.615	0

non-medium error count: 0

smart self-test log

num	test	status	segment	lifetime	lba_first_err	[sk asc asq]
	description		number	(hours)		
# 1	background short	completed	96	4	-	[- - -]
# 2	reserved(7)	completed	64	3	-	[- - -]

long (extended) self-test duration: 4839 seconds [80.7 minutes]