



Model: SEAGATE ST3300656SS
S/N: 3QP32EQ8

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-2**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE ST3300656SS**

Serial: **3QP32EQ8**

Size(Apparent): **300 GB, 300000000000 bytes**

Bus: **SAS**

Size(Real): **300 GB, 300000000000 bytes**

Disk Erasure Details

Start time: **2025/02/13 00:17:18**

End time: **2025/02/13 02:15:30**

Duration: **01:58:12**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **300000000000, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **126 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST3300656SS
S/N: 3QP32EQ8



Disk Erasure Report

Page 2 - Smart Data

smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE
product: ST3300656SS
revision: HS11
compliance: SPC-3
user capacity: 300,000,000,000 bytes [300 GB]
logical block size: 512 bytes
rotation rate: 15000 rpm
form factor: 3.5 inches
logical unit id: 0x5000c5001cd39d5b
serial number: 3QP32EQ8
device type: disk
transport protocol: SAS (SPL-3)
local time is: Thu Feb 13 02:15:31 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 35 C
drive trip temperature: 68 C

accumulated power on time, hours:minutes 55007:47
elements in grown defect list: 0

vendor (seagate cache) information

blocks sent to initiator = 3642303663
blocks received from initiator = 3268048444
blocks read from cache and sent to initiator = 7471686
number of read and write commands whose size <= segment size = 321739587
number of read and write commands whose size > segment size = 875718

vendor (seagate/hitachi) factory information

number of hours powered up = 55007.78
number of minutes until next internal smart test = 1

error counter log:

	errors corrected by			total	correction	gigabytes	total
	ecc		rereads/	errors	algorithm	processed	uncorrected
	fast	delayed	rewrites	corrected	invocations	[10 ⁹ bytes]	errors
read:	9600159	0	0	9600159	9600159	455.263	0
write:	0	0	0	0	0	8395.992	0
verify:	33729476	0	0	33729476	33729476	14212.894	0

non-medium error count: 45

smart self-test log

num	test	status	segment	lifetime	lba_first_err	[sk asc asq]
	description		number	(hours)		
# 1	background long	completed	16	36	- [- - -]	
# 2	background short	completed	16	35	- [- - -]	
# 3	background long	completed	16	11	- [- - -]	
# 4	background short	completed	16	10	- [- - -]	
# 5	background long	completed	16	1	- [- - -]	
# 6	background short	completed	16	1	- [- - -]	

long (extended) self-test duration: 2460 seconds [41.0 minutes]