



Model: SEAGATE ST1000NM0023

S/N: Z1W0M8SM

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-3**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE ST1000NM0023**

Serial: **Z1W0M8SM**

Size(Apparent): **1000 GB, 1000204886016 bytes**

Bus: **SAS**

Size(Real): **1000 GB, 1000204886016 bytes**

Disk Erasure Details

Start time: **2025/02/12 22:19:54**

End time: **2025/02/13 04:10:13**

Duration: **05:50:19**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **1000204886016, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **142 MB/sec**


Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST1000NM0023

S/N: Z1W0M8SM

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE
product: ST1000NM0023
revision: GS11
compliance: SPC-4
user capacity: 1,000,204,886,016 bytes [1.00 TB]
logical block size: 512 bytes
lu is fully provisioned
rotation rate: 7200 rpm
form factor: 3.5 inches
logical unit id: 0x5000c50057407af7
serial number: Z1W0M8SM
device type: disk
transport protocol: SAS (SPL-3)
local time is: Thu Feb 13 04:10:16 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 32 C
drive trip temperature: 60 C

accumulated power on time, hours:minutes 10229:00
manufactured in week 34 of year 2013
specified cycle count over device lifetime: 10000
accumulated start-stop cycles: 96
specified load-unload count over device lifetime: 300000
accumulated load-unload cycles: 1710
elements in grown defect list: 0

vendor (seagate cache) information

blocks sent to initiator = 2107104
blocks received from initiator = 3916258929
blocks read from cache and sent to initiator = 1082901
number of read and write commands whose size <= segment size = 8026823
number of read and write commands whose size > segment size = 20458

vendor (seagate/hitachi) factory information

number of hours powered up = 10229.00
number of minutes until next internal smart test = 21

error counter log:

	errors corrected by		total	correction	gigabytes	total
	ecc	rereads/	errors	algorithm	processed	uncorrected
	fast delayed	rewrites	corrected	invocations	[10^9 bytes]	errors
read:	1593136304	0	1593136304	0	2026.785	0
write:	0	0	0	0	4204.974	0
verify:	525610497	0	525610497	0	173.317	0

non-medium error count: 4

smart self-test log

num	test	status	segment	lifetime	lba_first_err	[sk asc asq]
	description		number	(hours)		
# 1	background long	completed	64	4	- [- - -]	
# 2	background short	completed	64	2	- [- - -]	

long (extended) self-test duration: 10800 seconds [180.0 minutes]



Model: SEAGATE ST1000NM0023

S/N: Z1W0M8SM

Disk Erasure Report

Page 3 - Smart Data

