



Model: TOSHIBA MK1001TRKB

S/N: 62E0A034FRZ9

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-2**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **TOSHIBA MK1001TRKB**

Serial: **62E0A034FRZ9**

Size(Apparent): **1000 GB, 1000204886016 bytes**

Bus: **SAS**

Size(Real): **1000 GB, 1000204886016 bytes**

Disk Erasure Details

Start time: **2025/02/12 22:19:50**

End time: **2025/02/13 06:07:35**

Duration: **07:47:45**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **1000204886016, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **106 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: TOSHIBA MK1001TRKB

S/N: 62E0A034FRZ9

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: TOSHIBA
product: MK1001TRKB
revision: DCAA
compliance: SPC-4
user capacity: 1,000,204,886,016 bytes [1.00 TB]
logical block size: 512 bytes
rotation rate: 7200 rpm
form factor: 3.5 inches
logical unit id: 0x5000039418c8c488
serial number: 62E0A034FRZ9
device type: disk
transport protocol: SAS (SPL-3)
local time is: Thu Feb 13 06:07:36 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 36 C
drive trip temperature: 65 C

accumulated power on time, hours:minutes 65659:37
manufactured in week 24 of year 2012
specified cycle count over device lifetime: 50000
accumulated start-stop cycles: 31
specified load-unload count over device lifetime: 600000
accumulated load-unload cycles: 0
elements in grown defect list: 2

error counter log:

	errors corrected by		total	correction	gigabytes	total
	ecc	rereads/	errors	algorithm	processed	uncorrected
	fast delayed	rewrites	corrected	invocations	[10 ⁹ bytes]	errors
read:	0 33	33	33	654	2919091.551	0
write:	0 82	82	82	410	47856.592	0
verify:	0 0	0	0	0	37304.763	0

non-medium error count: 10

smart self-test log

num	test description	status	segment number	lifetime (hours)	lba_first_err	[sk asc asq]
# 1	background long	completed	48	4	-	[- - -]
# 2	background short	completed	48	1	-	[- - -]
# 3	default	aborted (device reset ?)	48	1	-	[- - -]

long (extended) self-test duration: 8984 seconds [149.7 minutes]