



Model: WDC WD1003FBYX-1

S/N: WD-WMAW30356711

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-2**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **WDC WD1003FBYX-1**

Serial: **WD-WMAW30356711**

Size(Apparent): **1000 GB, 1000204886016 bytes**

Bus: **ATA**

Size(Real): **1000 GB, 1000204886016 bytes**

Disk Erasure Details

Start time: **2025/02/13 00:16:51**

End time: **2025/02/13 08:10:31**

Duration: **07:53:40**

Status: **ERASED**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **1000204886016, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **No hidden sectors**

HPA/DCO Size: **No hidden sectors**

Errors(pass/sync/verify): **0/0/0**

Throughput: **105 MB/sec**


Information:

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: WDC WD1003FBYX-1

S/N: WD-WMAW30356711

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

model family: Western Digital RE4
device model: WDC WD1003FBYX-18Y7B0
serial number: WD-WMAW30356711
lu wwn device id: 5 0014ee 25be1e5da
add. product id: DELL(tm)
firmware version: 01.01V02
user capacity: 1,000,204,886,016 bytes [1.00 TB]
sector size: 512 bytes logical/physical
rotation rate: 7200 rpm
device is: In smartctl database [for details use: -P show]
ata version is: ATA8-ACS (minor revision not indicated)
sata version is: SATA 2.6, 3.0 Gb/s
local time is: Thu Feb 13 08:10:32 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled

=== start of read smart data section ===

smart overall-health self-assessment test result: PASSED

general smart values:

offline data collection status: (0x84)Offline data collection activity
was suspended by an interrupting command from host.
auto offline data collection: Enabled.
self-test execution status: (0)The previous self-test routine completed
without error or no self-test has ever
been run.
total time to complete offline
data collection: (15600) seconds.
offline data collection
capabilities: (0x7b) SMART execute Offline immediate.
auto offline data collection on/off support.
suspend offline collection upon new
command.
offline surface scan supported.
self-test supported.
conveyance self-test supported.
selective self-test supported.
smart capabilities: (0x0003)Saves SMART data before entering
power-saving mode.
supports smart auto save timer.
error logging capability: (0x01)Error logging supported.
general purpose logging supported.
short self-test routine
recommended polling time: (2) minutes.
extended self-test routine
recommended polling time: (161) minutes.
conveyance self-test routine
recommended polling time: (5) minutes.
sct capabilities: (0x303f)SCT Status supported.
sct error recovery control supported.
sct feature control supported.
sct data table supported.

smart attributes data structure revision number: 16

vendor specific smart attributes with thresholds:

id#	attribute_name	flag	value	worst	thresh	type	updated	when_failed	raw_value
1	raw_read_error_rate	0x002f	200	200	051	pre-fail	always	-	23
3	spin_up_time	0x0027	168	168	021	pre-fail	always	-	4566
4	start_stop_count	0x0032	100	100	000	old_age	always	-	26
5	reallocated_sector_ct	0x0033	200	200	140	pre-fail	always	-	0



Model: WDC WD1003FBYX-1

S/N: WD-WMAW30356711



Disk Erasure Report

Page 3 - Smart Data

7	seek_error_rate	0x002e	200	200	000	old_age	always	-	0
9	power_on_hours	0x0032	001	001	000	old_age	always	-	76339
10	spin_retry_count	0x0032	100	253	000	old_age	always	-	0
11	calibration_retry_count	0x0032	100	253	000	old_age	always	-	0
12	power_cycle_count	0x0032	100	100	000	old_age	always	-	25
192	power-off_retract_count	0x0032	200	200	000	old_age	always	-	24
193	load_cycle_count	0x0032	200	200	000	old_age	always	-	1
194	temperature_celsius	0x0022	112	094	000	old_age	always	-	35 (min/max 11/36)
196	reallocated_event_count	0x0032	200	200	000	old_age	always	-	0
197	current_pending_sector	0x0032	200	200	000	old_age	always	-	0
198	offline_uncorrectable	0x0030	100	253	000	old_age	offline	-	0
199	udma_crc_error_count	0x0032	200	200	000	old_age	always	-	0
200	multi_zone_error_rate	0x0008	200	200	000	old_age	offline	-	0

smart error log version: 1
no errors logged

smart self-test log structure revision number 1

num	test_description	status	remaining	lifetime(hours)	lba_of_first_error
# 1	extended offline	completed without error	00%	4	-
# 2	extended offline	aborted by host	50%	2	-
# 3	short offline	completed without error	00%	1	-

smart selective self-test log data structure revision number 1

span	min_lba	max_lba	current_test_status
1	0	0	not_testing
2	0	0	not_testing
3	0	0	not_testing
4	0	0	not_testing
5	0	0	not_testing

selective self-test flags (0x0):

after scanning selected spans, do not read-scan remainder of disk.
if selective self-test is pending on power-up, resume after 0 minute delay.