



Model: SEAGATE ST3450857SS

S/N: 3SK08QGX00009025VU5Q

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-3**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE ST3450857SS**

Serial: **3SK08QGX00009025VU5Q**

Size(Apparent): **450 GB, 450098159616 bytes**

Bus: **SAS**

Size(Real): **450 GB, 450098159616 bytes**

Disk Erasure Details

Start time: **2025/02/13 05:49:50**

End time: **2025/02/13 08:17:43**

Duration: **02:27:53**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **450098159616, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **152 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST3450857SS

S/N: 3SK08QGX00009025VU5Q

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE
product: ST3450857SS
revision: 0008
compliance: SPC-3
user capacity: 450,098,159,616 bytes [450 GB]
logical block size: 512 bytes
rotation rate: 15000 rpm
form factor: 3.5 inches
logical unit id: 0x5000c50009391f93
serial number: 3SK08QGX00009025VU5Q
device type: disk
transport protocol: SAS (SPL-3)
local time is: Thu Feb 13 08:17:45 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Enabled

=== start of read smart data section ===

smart health status: OK

current drive temperature: 35 C
drive trip temperature: 68 C

accumulated power on time, hours:minutes 23602:10
elements in grown defect list: 2

vendor (seagate cache) information

blocks sent to initiator = 907412652
blocks received from initiator = 1758196057
blocks read from cache and sent to initiator = 39056
number of read and write commands whose size <= segment size = 7619
number of read and write commands whose size > segment size = 0

vendor (seagate/hitachi) factory information

number of hours powered up = 23602.17
number of minutes until next internal smart test = 59

error counter log:

	errors corrected by			total	correction	gigabytes	total
	ecc		rereads/	errors	algorithm	processed	uncorrected
	fast	delayed	rewrites	corrected	invocations	[10 ⁹ bytes]	errors
read:	5070468	0	0	5070468	5070468	236.962	0
write:	0	0	0	0	0	900.198	0

non-medium error count: 0

[gltsd (global logging target save disable) set. enable save with '-s on']
no self-tests have been logged