

Model: SEAGATE ST300MM0006
S/N: S0K3KL28



Disk Erasure Report

Page 1 - Erasure Status

Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-4**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE ST300MM0006**

Serial: **S0K3KL28**

Size(Apparent): **300 GB, 300000000000 bytes**

Bus: **SAS**

Size(Real): **300 GB, 300000000000 bytes**

Disk Erasure Details

Start time: **2025/02/13 12:12:20**

End time: **2025/02/13 13:55:51**

Duration: **01:43:31**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **300000000000, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **144 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST300MM0006

S/N: S0K3KL28

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE
product: ST300MM0006
revision: LS0C
compliance: SPC-4
user capacity: 300,000,000,000 bytes [300 GB]
logical block size: 512 bytes
lu is fully provisioned
rotation rate: 10000 rpm
form factor: 2.5 inches
logical unit id: 0x5000c5007ed3b8a7
serial number: S0K3KL28
device type: disk
transport protocol: SAS (SPL-3)
local time is: Thu Feb 13 13:55:53 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 29 C
drive trip temperature: 60 C

accumulated power on time, hours:minutes 75457:37
manufactured in week 48 of year 2014
specified cycle count over device lifetime: 10000
accumulated start-stop cycles: 143
specified load-unload count over device lifetime: 300000
accumulated load-unload cycles: 17954
elements in grown defect list: 0

vendor (seagate cache) information

blocks sent to initiator = 3089249712
blocks received from initiator = 1254834789
blocks read from cache and sent to initiator = 762155980
number of read and write commands whose size <= segment size = 644425956
number of read and write commands whose size > segment size = 218

vendor (seagate/hitachi) factory information

number of hours powered up = 75457.62
number of minutes until next internal smart test = 16


error counter log:

| | errors corrected by | | total | correction | gigabytes | total | |
|---------|---------------------|----------|-----------|-------------|--------------|-------------|---|
| | ecc | rereads/ | errors | algorithm | processed | uncorrected | |
| | fast delayed | rewrites | corrected | invocations | [10^9 bytes] | errors | |
| read: | 3916748461 | 0 | 0 | 3916748461 | 0 | 35415.182 | 0 |
| write: | 0 | 0 | 1 | 1 | 67778.306 | 0 | 0 |
| verify: | 2812403449 | 0 | 0 | 2812403449 | 0 | 122606.403 | 0 |

non-medium error count: 22

smart self-test log

| num | test | status | segment | lifetime | lba_first_err | [sk asc asq] |
|-----|------------------|-----------|---------|----------|---------------|--------------|
| | description | | number | (hours) | | |
| # 1 | background short | completed | 64 | 2 | - | [- - -] |
| # 2 | reserved(7) | completed | 48 | 2 | - | [- - -] |
| # 3 | background short | completed | 64 | 1 | - | [- - -] |



Model: SEAGATE ST300MM0006
S/N: S0K3KL28

Disk Erasure Report

Page 3 - Smart Data



long (extended) self-test duration: 1905 seconds [31.8 minutes]