

Model: SEAGATE ST32000645SS  
S/N: 9XH03CVM



# Disk Erasure Report

Page 1 - Erasure Status

## Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-4**

Contact Phone:

## Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

## Disk Information

Make/Model: **SEAGATE ST32000645SS**

Serial: **9XH03CVM**

Size(Apparent): **2000 GB, 2000398934016 bytes**

Bus: **SAS**

Size(Real): **2000 GB, 2000398934016 bytes**

## Disk Erasure Details

Start time: **2025/02/13 05:50:41**

End time: **2025/02/13 21:22:34**

Duration: **15:31:53**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

\*Bytes Erased: **2000398934016, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **107 MB/sec**


Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

\* bytes erased: The amount of drive that's been erased at least once

## Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST32000645SS

S/N: 9XH03CVM

# Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86\_64-linux-5.14.0-503.23.1.el9\_5.x86\_64] (local build)  
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE  
product: ST32000645SS  
revision: RS16  
compliance: SPC-4  
user capacity: 2,000,398,934,016 bytes [2.00 TB]  
logical block size: 512 bytes  
rotation rate: 7200 rpm  
form factor: 3.5 inches  
logical unit id: 0x5000c5004251e157  
serial number: 9XH03CVM  
device type: disk  
transport protocol: SAS (SPL-3)  
local time is: Thu Feb 13 21:22:36 2025 GMT  
smart support is: Available - device has SMART capability.  
smart support is: Enabled  
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 35 C  
drive trip temperature: 68 C

accumulated power on time, hours:minutes 26813:02  
manufactured in week 31 of year 2012  
specified cycle count over device lifetime: 10000  
accumulated start-stop cycles: 2  
specified load-unload count over device lifetime: 300000  
accumulated load-unload cycles: 62446  
elements in grown defect list: 0

vendor (seagate cache) information

blocks sent to initiator = 671263659  
blocks received from initiator = 2327964421  
blocks read from cache and sent to initiator = 3980048992  
number of read and write commands whose size <= segment size = 9287549  
number of read and write commands whose size > segment size = 0

vendor (seagate/hitachi) factory information

number of hours powered up = 26813.05  
number of minutes until next internal smart test = 59

error counter log:

	errors corrected by			total	correction	gigabytes	total
	ecc	rereads/		errors	algorithm	processed	uncorrected
	fast   delayed	rewrites	corrected		invocations	[10^9 bytes]	errors
read:	2762491315	0	0	2762491315	0	17335.393	0
write:	0	0	0	0	0	5598.169	0
verify:	992807309	0	0	992807309	0	274026.688	0

non-medium error count: 11454

no self-tests have been logged