



Model: WD WD6002BKTG

S/N: WX41E34CW66

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-0**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **WD WD6002BKTG**

Serial: **WX41E34CW66**

Size(Apparent): **600 GB, 600127266816 bytes**

Bus: **SAS**

Size(Real): **600 GB, 600127266816 bytes**

Disk Erasure Details

Start time: **2025/02/14 15:36:21**

End time: **2025/02/14 15:38:21**

Duration: **00:02:00**

Status: **FAILED**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **409600000, (0.06%)**

Rounds(completed/requested): **0/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **1/1/0**

Throughput: **3413 KB/sec**

Information: **Warning** HPA/DCO data unavailable, can not determine hidden sector status.

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: WD WD6002BKTG

S/N: WX41E34CW66



Disk Erasure Report

Page 2 - Smart Data

smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.22.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: WD
product: WD6002BKTG
revision: D1P3
compliance: SPC-4
user capacity: 600,127,266,816 bytes [600 GB]
logical block size: 512 bytes
rotation rate: 10000 rpm
form factor: 2.5 inches
logical unit id: 0x50014ee755956b94
serial number: WX41E34CW66
device type: disk
transport protocol: SAS (SPL-3)
local time is: Fri Feb 14 15:38:23 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 13 C
drive trip temperature: 50 C

accumulated power on time, hours:minutes 79512:47
manufactured in week 21 of year 2014
specified cycle count over device lifetime: 1048576
accumulated start-stop cycles: 24
specified load-unload count over device lifetime: 1114112
accumulated load-unload cycles: 27045
elements in grown defect list: 21

error counter log:

	errors corrected by	total errors	correction algorithm	gigabytes processed	total uncorrected errors
	ecc	rereads/rewrites		[10^9 bytes]	
read:	1010969518	173 64464	1010969691	385 38168.782	213
write:	952788369	33 7876	952788402	39 76866.906	0
verify:	4737955	1379 10879	4739334	1379 9925.143	0

non-medium error count: 314

smart self-test log

num	test description	status	segment number	lifetime (hours)	lba_first_err	[sk asc asq]
# 1	background short	completed	48	7	-	[- - -]
# 2	reserved(7)	completed	32	7	-	[- - -]
# 3	background short	completed	48	5	-	[- - -]

long (extended) self-test duration: 4144 seconds [69.1 minutes]