



Model: SEAGATE ST3146356SS

S/N: 3QN3JQ0X

# Disk Erasure Report

Page 1 - Erasure Status



## Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-2**

Contact Phone:

## Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

## Disk Information

Make/Model: **SEAGATE ST3146356SS**

Serial: **3QN3JQ0X**

Size(Apparent): **146 GB, 146815733760 bytes**

Bus: **SAS**

Size(Real): **146 GB, 146815733760 bytes**

## Disk Erasure Details

Start time: **2025/02/14 15:33:34**

End time: **2025/02/14 16:29:06**

Duration: **00:55:32**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

\*Bytes Erased: **146815733760, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **132 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

\* bytes erased: The amount of drive that's been erased at least once

## Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST3146356SS

S/N: 3QN3JQ0X

# Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86\_64-linux-5.14.0-503.23.1.el9\_5.x86\_64] (local build)  
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE  
product: ST3146356SS  
revision: HS0F  
compliance: SPC-3  
user capacity: 146,815,733,760 bytes [146 GB]  
logical block size: 512 bytes  
rotation rate: 15000 rpm  
logical unit id: 0x5000c5001dbf9cb3  
serial number: 3QN3JQ0X  
device type: disk  
transport protocol: SAS (SPL-3)  
local time is: Fri Feb 14 16:29:07 2025 GMT  
smart support is: Available - device has SMART capability.  
smart support is: Enabled  
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 35 C  
drive trip temperature: 68 C

accumulated power on time, hours:minutes 30436:37  
elements in grown defect list: 0

vendor (seagate cache) information

blocks sent to initiator = 1971192396  
blocks received from initiator = 1163031316  
blocks read from cache and sent to initiator = 3706447028  
number of read and write commands whose size <= segment size = 3680027591  
number of read and write commands whose size > segment size = 557

vendor (seagate/hitachi) factory information

number of hours powered up = 30436.62  
number of minutes until next internal smart test = 4

error counter log:

	errors corrected by	total	correction	gigabytes	total		
	ecc	rereads/	errors	processed	uncorrected		
	fast   delayed	rewrites	corrected	invocations	[10^9 bytes] errors		
read:	1004589159	0	0	1004589159	1004589159	147248.771	0
write:	0	0	0	0	203396.436	0	0
verify:	103352273	0	0	103352273	103352273	66670.598	0

non-medium error count: 32334

smart self-test log

num	test	status	segment	lifetime	lba_first_err	[sk asc asq]
			number	(hours)		
# 1	background short	completed	16	16941	-	[- - -]
# 2	background short	completed	16	0	-	[- - -]

long (extended) self-test duration: 1740 seconds [29.0 minutes]