



Model: SEAGATE ST3146356SS
S/N: 3QN2XTJ6



Disk Erasure Report

Page 1 - Erasure Status

Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-2**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE ST3146356SS**

Serial: **3QN2XTJ6**

Size(Apparent): **146 GB, 146815733760 bytes**

Bus: **SAS**

Size(Real): **146 GB, 146815733760 bytes**

Disk Erasure Details

Start time: **2025/02/14 15:33:01**

End time: **2025/02/14 16:30:16**

Duration: **00:57:15**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **146815733760, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **128 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST3146356SS
S/N: 3QN2XTJ6



Disk Erasure Report

Page 2 - Smart Data

smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE
product: ST3146356SS
revision: HS0F
compliance: SPC-3
user capacity: 146,815,733,760 bytes [146 GB]
logical block size: 512 bytes
rotation rate: 15000 rpm
logical unit id: 0x5000c5001cbfe14f
serial number: 3QN2XTJ6
device type: disk
transport protocol: SAS (SPL-3)
local time is: Fri Feb 14 16:30:18 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 39 C
drive trip temperature: 68 C

accumulated power on time, hours:minutes 42903:54
elements in grown defect list: 1

vendor (seagate cache) information

blocks sent to initiator = 1211117733
blocks received from initiator = 989186390
blocks read from cache and sent to initiator = 3526239545
number of read and write commands whose size <= segment size = 2899626163
number of read and write commands whose size > segment size = 0

vendor (seagate/hitachi) factory information

number of hours powered up = 42903.90
number of minutes until next internal smart test = 2

error counter log:

	errors corrected by	total errors	correction algorithm	gigabytes processed	total uncorrected errors	
	ecc	rereads/rewrites		[10^9 bytes]		
	fast delayed					
read:	359183727 1	0	359183728	359183728	85311.839	0
write:	0 0	0	0	1	198849.150	1
verify:	37524864 0	0	37524864	37524865	88958.076	1

non-medium error count: 290

smart self-test log

num	test	status	segment number	lifetime (hours)	lba_first_err	[sk asc asq]
# 1	background short	completed	16	29516	-	[- - -]
# 2	background short	completed	16	29516	-	[- - -]
# 3	background long	completed	16	1	-	[- - -]
# 4	background short	completed	16	0	-	[- - -]

long (extended) self-test duration: 1740 seconds [29.0 minutes]