

Model: SEAGATE ST3600057SS  
S/N: 6SL2EQHJ



# Disk Erasure Report

Page 1 - Erasure Status

## Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-4**

Contact Phone:

## Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

## Disk Information

Make/Model: **SEAGATE ST3600057SS**

Serial: **6SL2EQHJ**

Size(Apparent): **600 GB, 600127266816 bytes**

Bus: **SAS**

Size(Real): **600 GB, 600127266816 bytes**

## Disk Erasure Details

Start time: **2025/02/14 15:43:30**

End time: **2025/02/14 18:01:07**

Duration: **02:17:37**

Status: **FAILED**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

\*Bytes Erased: **600127266816, (100.00%)**

Rounds(completed/requested): **0/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **1/0/0**

Throughput: **145 MB/sec**


Information: **Warning** HPA/DCO data unavailable, can not determine hidden sector status.

\* bytes erased: The amount of drive that's been erased at least once

## Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST3600057SS  
S/N: 6SL2EQHJ



# Disk Erasure Report

Page 2 - Smart Data

smartctl 7.2 2020-12-30 r5155 [x86\_64-linux-5.14.0-503.23.1.el9\_5.x86\_64] (local build)  
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE  
product: ST3600057SS  
revision: ES64  
compliance: SPC-3  
user capacity: 600,127,266,816 bytes [600 GB]  
logical block size: 512 bytes  
rotation rate: 15000 rpm  
form factor: 3.5 inches  
logical unit id: 0x5000c50043825cc3  
serial number: 6SL2EQHJ  
device type: disk  
transport protocol: SAS (SPL-3)  
local time is: Fri Feb 14 18:01:14 2025 GMT  
smart support is: Available - device has SMART capability.  
smart support is: Enabled  
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: FAILURE PREDICTION THRESHOLD EXCEEDED: ascq=0x5 [asc=5d, ascq=5]

current drive temperature: 38 C  
drive trip temperature: 68 C

accumulated power on time, hours:minutes 32513:42  
elements in grown defect list: 2031

vendor (seagate cache) information

blocks sent to initiator = 2139589464  
blocks received from initiator = 3312112169  
blocks read from cache and sent to initiator = 2899083376  
number of read and write commands whose size <= segment size = 3990281981  
number of read and write commands whose size > segment size = 0

vendor (seagate/hitachi) factory information

number of hours powered up = 32513.70  
number of minutes until next internal smart test = 59

error counter log:

	errors corrected by			total	correction	gigabytes	total
	ecc		rereads/	errors	algorithm	processed	uncorrected
	fast	delayed	rewrites	corrected	invocations	[10^9 bytes]	errors
read:	3602887116	85	0	3602887201	3602887235	496506.253	34
write:	0	0	3	3	4	159204.735	10
verify:	4146380251	91	0	4146380342	4146380510	368762.406	108

non-medium error count: 359

smart self-test log

num	test	status		segment	lifetime	lba_first_err	[sk asc asq]
	description			number	(hours)		
# 1	background long	completed		16	5	-	[- - -]

long (extended) self-test duration: 6400 seconds [106.7 minutes]