



Model: SEAGATE ST3600057SS
S/N: 6SL2RNDL



Disk Erasure Report

Page 1 - Erasure Status

Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-4**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE ST3600057SS**

Serial: **6SL2RNDL**

Size(Apparent): **600 GB, 600127266816 bytes**

Bus: **SAS**

Size(Real): **600 GB, 600127266816 bytes**

Disk Erasure Details

Start time: **2025/02/14 15:43:02**

End time: **2025/02/14 19:02:06**

Duration: **03:19:04**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **600127266816, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **150 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST3600057SS
S/N: 6SL2RNDL



Disk Erasure Report

Page 2 - Smart Data

smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE
product: ST3600057SS
revision: ES65
compliance: SPC-3
user capacity: 600,127,266,816 bytes [600 GB]
logical block size: 512 bytes
rotation rate: 15000 rpm
form factor: 3.5 inches
logical unit id: 0x5000c5004758028b
serial number: 6SL2RNDL
device type: disk
transport protocol: SAS (SPL-3)
local time is: Fri Feb 14 19:02:08 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 36 C
drive trip temperature: 68 C

accumulated power on time, hours:minutes 17210:43
elements in grown defect list: 0

vendor (seagate cache) information

blocks sent to initiator = 3077577312
blocks received from initiator = 373566580
blocks read from cache and sent to initiator = 1074020084
number of read and write commands whose size <= segment size = 3964830597
number of read and write commands whose size > segment size = 173

vendor (seagate/hitachi) factory information

number of hours powered up = 17210.72
number of minutes until next internal smart test = 59

error counter log:

	errors corrected by ecc	total errors	correction algorithm	gigabytes processed	total uncorrected	
	fast delayed	rereads/ rewrites	invocations	[10^9 bytes]	errors	
read:	1540448856	0	0	1540448856	24318.795	0
write:	0	0	0	88726.293	0	0
verify:	2142362075	9	0	2142362084	267270.296	1

non-medium error count: 33

smart self-test log

num	test	status	segment number	lifetime (hours)	lba_first_err	[sk asc asq]
# 1	background long	completed	32	5	-	[- - -]
# 2	background long	completed	32	4	-	[- - -]
# 3	background short	completed	32	3	-	[- - -]

long (extended) self-test duration: 6400 seconds [106.7 minutes]