



Model: WD WD6001BKHG

S/N: WX21EB1RC484

# Disk Erasure Report

Page 1 - Erasure Status



## Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-0**

Contact Phone:

## Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

## Disk Information

Make/Model: **WD WD6001BKHG**

Serial: **WX21EB1RC484**

Size(Apparent): **600 GB, 600127266816 bytes**

Bus: **SAS**

Size(Real): **600 GB, 600127266816 bytes**

## Disk Erasure Details

Start time: **2025/02/14 15:36:09**

End time: **2025/02/14 19:08:50**

Duration: **03:32:41**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

\*Bytes Erased: **600127266816, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **141 MB/sec**


Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

\* bytes erased: The amount of drive that's been erased at least once

## Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: WD WD6001BKHG

S/N: WX21EB1RC484



# Disk Erasure Report

Page 2 - Smart Data

smartctl 7.2 2020-12-30 r5155 [x86\_64-linux-5.14.0-503.22.1.el9\_5.x86\_64] (local build)  
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: WD  
product: WD6001BKHG  
revision: D1S2  
compliance: SPC-4  
user capacity: 600,127,266,816 bytes [600 GB]  
logical block size: 512 bytes  
rotation rate: 10000 rpm  
form factor: 2.5 inches  
logical unit id: 0x50000c0f01008ec4  
serial number: WX21EB1RC484  
device type: disk  
transport protocol: SAS (SPL-3)  
local time is: Fri Feb 14 19:08:52 2025 GMT  
smart support is: Available - device has SMART capability.  
smart support is: Enabled  
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 29 C  
drive trip temperature: 64 C

accumulated power on time, hours:minutes 92991:57  
manufactured in week 01 of year 2010  
specified cycle count over device lifetime: 1048576  
accumulated start-stop cycles: 2  
specified load-unload count over device lifetime: 1114112  
accumulated load-unload cycles: 5  
elements in grown defect list: 0

error counter log:

	errors corrected by		total	correction	gigabytes	total
	ecc	rereads/	errors	algorithm	processed	uncorrected
	fast   delayed	rewrites	corrected	invocations	[10^9 bytes]	errors
read:	9412859 12047	0	9424906	12047	98214.466	0
write:	37758 232908	0	270666	232908	157688.049	0
verify:	17509 336	0	17845	336	9715.731	0

non-medium error count: 16

no self-tests have been logged