



Model: WD WD6001BKHG

S/N: WXJ1E23ALHR7

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-0**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **WD WD6001BKHG**

Serial: **WXJ1E23ALHR7**

Size(Apparent): **600 GB, 600127266816 bytes**

Bus: **SAS**

Size(Real): **600 GB, 600127266816 bytes**

Disk Erasure Details

Start time: **2025/02/14 15:37:35**

End time: **2025/02/14 19:45:31**

Duration: **04:07:56**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **600127266816, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **121 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: WD WD6001BKHG

S/N: WXJ1E23ALHR7



Disk Erasure Report

Page 2 - Smart Data

smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.22.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: WD
product: WD6001BKHG
revision: D1S6
compliance: SPC-4
user capacity: 600,127,266,816 bytes [600 GB]
logical block size: 512 bytes
rotation rate: 10000 rpm
form factor: 2.5 inches
logical unit id: 0x50000c0f022be460
serial number: WXJ1E23ALHR7
device type: disk
transport protocol: SAS (SPL-3)
local time is: Fri Feb 14 19:45:32 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 29 C
drive trip temperature: 64 C

accumulated power on time, hours:minutes 90445:00
manufactured in week 41 of year 2013
specified cycle count over device lifetime: 1048576
accumulated start-stop cycles: 1
specified load-unload count over device lifetime: 1114112
accumulated load-unload cycles: 29
elements in grown defect list: 0

error counter log:

	errors corrected by ecc	fast delayed	rereads/ rewrites	total errors corrected	correction algorithm invocations	gigabytes processed [10^9 bytes]	total uncorrected errors
read:	2119475469	33	1639	2119475502	33	86210.537	0
write:	2000298884	14	1969	2000298898	14	137277.400	0
verify:	8054877	5	111	8054882	5	16889.271	0

non-medium error count: 29

no self-tests have been logged