



Model: SEAGATE ST9600204SS
S/N: 6WN0VCBY



Disk Erasure Report

Page 1 - Erasure Status

Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-0**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE ST9600204SS**

Serial: **6WN0VCBY**

Size(Apparent): **600 GB, 600127266816 bytes**

Bus: **SAS**

Size(Real): **600 GB, 600127266816 bytes**

Disk Erasure Details

Start time: **2025/02/14 15:36:25**

End time: **2025/02/14 20:23:00**

Duration: **04:46:35**

Status: **FAILED**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **600127266816, (100.00%)**

Rounds(completed/requested): **0/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **1/0/0**

Throughput: **99 MB/sec**

Information: **Warning** HPA/DCO data unavailable, can not determine hidden sector status.

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST9600204SS
S/N: 6WN0VCBY



Disk Erasure Report

Page 2 - Smart Data

smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.22.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE
product: ST9600204SS
revision: FM0A
compliance: SPC-3
user capacity: 600,127,266,816 bytes [600 GB]
logical block size: 512 bytes
rotation rate: 10000 rpm
form factor: 2.5 inches
logical unit id: 0x5000c5003b238bdb
serial number: 6WN0VCBY
device type: disk
transport protocol: SAS (SPL-3)
local time is: Fri Feb 14 20:23:02 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 31 C
drive trip temperature: 68 C

accumulated power on time, hours:minutes 36286:06
manufactured in week 23 of year 2011
specified cycle count over device lifetime: 10000
accumulated start-stop cycles: 13
specified load-unload count over device lifetime: 300000
accumulated load-unload cycles: 13
elements in grown defect list: 2

vendor (seagate cache) information

blocks sent to initiator = 505529028
blocks received from initiator = 2134346725
blocks read from cache and sent to initiator = 454515148
number of read and write commands whose size <= segment size = 3668909976
number of read and write commands whose size > segment size = 0

vendor (seagate/hitachi) factory information

number of hours powered up = 36286.10
number of minutes until next internal smart test = 59

error counter log:

| | errors corrected by | | total | correction | gigabytes | total |
|---------|---------------------|----------|-----------|-------------|--------------|-------------|
| | ecc | rereads/ | errors | algorithm | processed | uncorrected |
| | fast delayed | rewrites | corrected | invocations | [10^9 bytes] | errors |
| read: | 3265361221 | 29 | 0 | 3265361250 | 3265361254 | 905668.227 |
| write: | 0 | 0 | 1645 | 1645 | 1647 | 247032.548 |
| verify: | 1042265291 | 5 | 0 | 1042265296 | 1042265296 | 375036.319 |

non-medium error count: 17711

smart self-test log

| num | test | status | segment | lifetime | lba_first_err | [sk asc asq] |
|-----|------------------|-----------|---------|----------|---------------|--------------|
| | description | | number | (hours) | | |
| # 1 | background long | completed | 16 | 6 | - | [- - -] |
| # 2 | background long | completed | 16 | 2 | - | [- - -] |
| # 3 | background short | completed | 16 | 1 | - | [- - -] |

long (extended) self-test duration: 6176 seconds [102.9 minutes]



Model: SEAGATE ST9600204SS
S/N: 6WN0VCBY

Disk Erasure Report

Page 3 - Smart Data

