



Model: HDS721010KLA33R

S/N: GTA070PBJRU0TF

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-3**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **HDS721010KLA33R**

Serial: **GTA070PBJRU0TF**

Size(Apparent): **1000 GB, 1000204886016 bytes**

Bus: **UNK**

Size(Real): **1000 GB, 1000204886016 bytes**

Disk Erasure Details

Start time: **2025/02/14 15:34:36**

End time: **2025/02/15 04:06:35**

Duration: **12:31:59**

Status: **ERASED**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **1000204886016, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **No hidden sectors**

HPA/DCO Size: **No hidden sectors**

Errors(pass/sync/verify): **0/0/0**

Throughput: **66 MB/sec**


Information:

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: HDS721010KLA33R

S/N: GTA070PBJRU0TF

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

device model: HDS721010KLA33R RSD HUA
serial number: GTA070PBJRU0TF
lu wwn device id: 5 000cca 21ee68d1d
firmware version: GKAOA9JA
user capacity: 1,000,204,886,016 bytes [1.00 TB]
sector size: 512 bytes logical/physical
device is: Not in smartctl database [for details use: -P showall]
ata version is: ATA/ATAPI-7 T13/1532D revision 1
local time is: Sat Feb 15 04:06:37 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled

=== start of read smart data section ===

smart overall-health self-assessment test result: PASSED

general smart values:

offline data collection status: (0x80)Offline data collection activity
was never started.

auto offline data collection: Enabled.

self-test execution status: (0)The previous self-test routine completed
without error or no self-test has ever
been run.

total time to complete offline
data collection: (15354) seconds.

offline data collection

capabilities: (0x5b) SMART execute Offline immediate.

auto offline data collection on/off support.

suspend offline collection upon new
command.

offline surface scan supported.

self-test supported.

no conveyance self-test supported.

selective self-test supported.

smart capabilities: (0x0003)Saves SMART data before entering
power-saving mode.

supports smart auto save timer.

error logging capability: (0x01)Error logging supported.

general purpose logging supported.

short self-test routine

recommended polling time: (1) minutes.

extended self-test routine

recommended polling time: (255) minutes.

sct capabilities: (0x003f)SCT Status supported.

sct error recovery control supported.

sct feature control supported.

sct data table supported.

smart attributes data structure revision number: 16

vendor specific smart attributes with thresholds:

id#	attribute_name	flag	value	worst	thresh	type	updated	when_failed	raw_value
1	raw_read_error_rate	0x000b	100	100	016	pre-fail	always	-	0
2	throughput_performance	0x0005	130	130	054	pre-fail	offline	-	152
3	spin_up_time	0x0007	103	103	024	pre-fail	always	-	679 (average 675)
4	start_stop_count	0x0012	100	100	000	old_age	always	-	214
5	reallocated_sector_ct	0x0033	100	100	005	pre-fail	always	-	1
7	seek_error_rate	0x000b	100	100	067	pre-fail	always	-	0
8	seek_time_performance	0x0005	134	134	020	pre-fail	offline	-	32
9	power_on_hours	0x0012	086	086	000	old_age	always	-	103903
10	spin_retry_count	0x0013	100	100	060	pre-fail	always	-	0
12	power_cycle_count	0x0032	100	100	000	old_age	always	-	23



Model: HDS721010KLA33R

S/N: GTA070PBJRU0TF



Disk Erasure Report

Page 3 - Smart Data

192	power-off_retract_count	0x0032	100	100	000	old_age	always	-	421
193	load_cycle_count	0x0012	100	100	000	old_age	always	-	421
194	temperature_celsius	0x0002	157	157	000	old_age	always	-	38 (min/max 7/65)
196	reallocated_event_count	0x0032	100	100	000	old_age	always	-	1
197	current_pending_sector	0x0022	100	100	000	old_age	always	-	0
198	offline_uncorrectable	0x0008	100	100	000	old_age	offline	-	0
199	udma_crc_error_count	0x000a	200	200	000	old_age	always	-	0

smart error log version: 1
no errors logged

smart self-test log structure revision number 1

num	test_description	status	remaining	lifetime(hours)	lba_of_first_error
# 1	short captive	completed without error	00%	34506	-

smart selective self-test log data structure revision number 1

span	min_lba	max_lba	current_test_status
1	0	0	not_testing
2	0	0	not_testing
3	0	0	not_testing
4	0	0	not_testing
5	0	0	not_testing

selective self-test flags (0x0):

after scanning selected spans, do not read-scan remainder of disk.
if selective self-test is pending on power-up, resume after 0 minute delay.