



Model: SEAGATE ST3000NM0023

S/N: S1Z059G00000K4468F71

# Disk Erasure Report

Page 1 - Erasure Status



## Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-3**

Contact Phone:

## Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

## Disk Information

Make/Model: **SEAGATE ST3000NM0023**

Serial: **S1Z059G00000K4468F71**

Size(Apparent): **3000 GB, 3000592982016 bytes**

Bus: **SAS**

Size(Real): **3000 GB, 3000592982016 bytes**

## Disk Erasure Details

Start time: **2025/02/14 15:35:06**

End time: **2025/02/15 10:51:13**

Duration: **19:16:07**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

\*Bytes Erased: **3000592982016, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **129 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

\* bytes erased: The amount of drive that's been erased at least once

## Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST3000NM0023

S/N: S1Z059G00000K4468F71

# Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86\_64-linux-5.14.0-503.23.1.el9\_5.x86\_64] (local build)  
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE  
product: ST3000NM0023  
revision: 0004  
compliance: SPC-4  
user capacity: 3,000,592,982,016 bytes [3.00 TB]  
logical block size: 512 bytes  
lu is fully provisioned  
rotation rate: 7200 rpm  
form factor: 3.5 inches  
logical unit id: 0x5000c5007676413f  
serial number: S1Z059G00000K4468F71  
device type: disk  
transport protocol: SAS (SPL-3)  
local time is: Sat Feb 15 10:51:15 2025 GMT  
smart support is: Available - device has SMART capability.  
smart support is: Enabled  
temperature warning: Enabled

=== start of read smart data section ===

smart health status: OK

current drive temperature: 31 C  
drive trip temperature: 60 C

accumulated power on time, hours:minutes 3415:31  
manufactured in week 24 of year 2014  
specified cycle count over device lifetime: 10000  
accumulated start-stop cycles: 167  
specified load-unload count over device lifetime: 300000  
accumulated load-unload cycles: 3562  
elements in grown defect list: 0

vendor (seagate cache) information

blocks sent to initiator = 1566000783  
blocks received from initiator = 3131140168  
blocks read from cache and sent to initiator = 10008  
number of read and write commands whose size <= segment size = 30989  
number of read and write commands whose size > segment size = 30097

vendor (seagate/hitachi) factory information

number of hours powered up = 3415.52  
number of minutes until next internal smart test = 28

error counter log:

	errors corrected by	total	correction	gigabytes	total
	ecc	errors	algorithm	processed	uncorrected
	fast   delayed	rewrites	corrected	invocations	errors
read:	2920241585	0	0	2920241585	0
write:	0	0	0	0	0

[10^9 bytes]

1703.736  
6010.951

non-medium error count: 8

[gltsd (global logging target save disable) set. enable save with '-s on']  
no self-tests have been logged