



Model: SEAGATE ST3600057SS
S/N: 3SL1DQ3X



Disk Erasure Report

Page 1 - Erasure Status

Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-2**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE ST3600057SS**

Serial: **3SL1DQ3X**

Size(Apparent): **600 GB, 600127266816 bytes**

Bus: **SAS**

Size(Real): **600 GB, 600127266816 bytes**

Disk Erasure Details

Start time: **2025/02/15 10:39:28**

End time: **2025/02/15 12:51:27**

Duration: **02:11:59**

Status: **FAILED**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **600127266816, (100.00%)**

Rounds(completed/requested): **0/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **1/0/0**

Throughput: **151 MB/sec**

Information: **Warning** HPA/DCO data unavailable, can not determine hidden sector status.

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST3600057SS
S/N: 3SL1DQ3X



Disk Erasure Report

Page 2 - Smart Data

smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE
product: ST3600057SS
revision: ES64
compliance: SPC-3
user capacity: 600,127,266,816 bytes [600 GB]
logical block size: 512 bytes
rotation rate: 15000 rpm
form factor: 3.5 inches
logical unit id: 0x5000c5002872ec5b
serial number: 3SL1DQ3X
device type: disk
transport protocol: SAS (SPL-3)
local time is: Sat Feb 15 12:51:28 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 45 C
drive trip temperature: 68 C

accumulated power on time, hours:minutes 18089:04
elements in grown defect list: 29

vendor (seagate cache) information

blocks sent to initiator = 3561001076
blocks received from initiator = 2904611066
blocks read from cache and sent to initiator = 264189480
number of read and write commands whose size <= segment size = 428762539
number of read and write commands whose size > segment size = 2058

vendor (seagate/hitachi) factory information

number of hours powered up = 18089.07
number of minutes until next internal smart test = 59

error counter log:

	errors corrected by ecc	errors corrected by rereads/ rewrites	total errors corrected	correction algorithm invocations	gigabytes processed [10^9 bytes]	total uncorrected errors
read:	221599273	4	0	221599277	5361.933	5
write:	0	0	1	5	27988.451	7
verify:	1260466514	50	0	1260466564	232070.320	17

non-medium error count: 241

smart self-test log

num	test description	status	segment number	lifetime (hours)	lba_first_err	[sk asc asq]
# 1	background long	completed	16	5	-	[- - -]
# 2	background short	completed	16	5	-	[- - -]

long (extended) self-test duration: 6400 seconds [106.7 minutes]