



Model: SEAGATE ST600MM0088

S/N: S421BWTX

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-0**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE ST600MM0088**

Serial: **S421BWTX**

Size(Apparent): **600 GB, 600127266816 bytes**

Bus: **SAS**

Size(Real): **600 GB, 600127266816 bytes**

Disk Erasure Details

Start time: **2025/02/15 10:39:00**

End time: **2025/02/15 14:00:41**

Duration: **03:21:41**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **600127266816, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **148 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST600MM0088

S/N: S421BWTX

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.22.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE
product: ST600MM0088
revision: TT31
compliance: SPC-4
user capacity: 600,127,266,816 bytes [600 GB]
logical block size: 512 bytes
formatted with type 2 protection
8 bytes of protection information per logical block
lu is fully provisioned
rotation rate: 10000 rpm
form factor: 2.5 inches
logical unit id: 0x5000c50097036ceb
serial number: S421BWTX
device type: disk
transport protocol: SAS (SPL-3)
local time is: Sat Feb 15 14:00:43 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

grown defects during certification <not available>
total blocks reassigned during format <not available>
total new blocks reassigned = 1
power on minutes since format <not available>
current drive temperature: 30 C
drive trip temperature: 60 C

accumulated power on time, hours:minutes 71491:16
manufactured in week 16 of year 2016
specified cycle count over device lifetime: 10000
accumulated start-stop cycles: 11
specified load-unload count over device lifetime: 300000
accumulated load-unload cycles: 2988
elements in grown defect list: 1

vendor (seagate cache) information
blocks sent to initiator = 1646557548
blocks received from initiator = 3399016738
blocks read from cache and sent to initiator = 801167250
number of read and write commands whose size <= segment size = 2362925495
number of read and write commands whose size > segment size = 0


vendor (seagate/hitachi) factory information
number of hours powered up = 71491.27
number of minutes until next internal smart test = 45

error counter log:

	errors corrected by ecc	errors corrected by fast delayed	rereads/ rewrites	total errors corrected	correction algorithm invocations	gigabytes processed [10^9 bytes]	total uncorrected errors
read:	115192657	186	0	115192843	186	1097300.406	0
write:	0	0	342	342	344	341341.113	3
verify:	3359689546	3	0	3359689549	3	256985.898	0

non-medium error count: 35

no self-tests have been logged



Model: SEAGATE ST600MM0088

S/N: S421BWTX

Disk Erasure Report

Page 3 - Smart Data

