



Model: WD WD6001BKHG

S/N: WXB1E62DZL79

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-0**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **WD WD6001BKHG**

Serial: **WXB1E62DZL79**

Size(Apparent): **600 GB, 600127266816 bytes**

Bus: **SAS**

Size(Real): **600 GB, 600127266816 bytes**

Disk Erasure Details

Start time: **2025/02/15 10:39:12**

End time: **2025/02/15 14:21:54**

Duration: **03:42:42**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **600127266816, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **134 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: WD WD6001BKHG

S/N: WXB1E62DZL79



Disk Erasure Report

Page 2 - Smart Data

smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.22.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: WD
product: WD6001BKHG
revision: D1S4
compliance: SPC-4
user capacity: 600,127,266,816 bytes [600 GB]
logical block size: 512 bytes
rotation rate: 10000 rpm
form factor: 2.5 inches
logical unit id: 0x50000c0f02651d04
serial number: WXB1E62DZL79
device type: disk
transport protocol: SAS (SPL-3)
local time is: Sat Feb 15 14:21:56 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Enabled

=== start of read smart data section ===

smart health status: OK

current drive temperature: 30 C
drive trip temperature: 64 C

accumulated power on time, hours:minutes 90206:52
manufactured in week 01 of year 2010
specified cycle count over device lifetime: 1048576
accumulated start-stop cycles: 12
specified load-unload count over device lifetime: 1114112
accumulated load-unload cycles: 96
elements in grown defect list: 0

error counter log:

	errors corrected by	total	correction	gigabytes	total	
	ecc	errors	algorithm	processed	uncorrected	
	fast delayed	rereads/ rewrites	corrected	invocations	[10^9 bytes] errors	
read:	24146526 116565	0	24263091	116565	212230.453	0
write:	137865 951572	0	1089437	951572	321978.945	0
verify:	113933 47939	0	161872	47939	9170.295	0

non-medium error count: 62

smart self-test log

num	test	status	segment	lifetime	lba_first_err	[sk asc asq]
	description		number	(hours)		
# 1	background short	completed	32	2	-	[- - -]
# 2	background long	aborted (by user command)	32	2	-	[- - -]

long (extended) self-test duration: 4144 seconds [69.1 minutes]