



Model: SEAGATE ST91000640SS
S/N: 9XG1KLVH



Disk Erasure Report

Page 1 - Erasure Status

Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-5**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE ST91000640SS**

Serial: **9XG1KLVH**

Size(Apparent): **1000 GB, 1000204886016 bytes**

Bus: **SAS**

Size(Real): **1000 GB, 1000204886016 bytes**

Disk Erasure Details

Start time: **2025/02/15 10:35:37**

End time: **2025/02/15 20:43:55**

Duration: **10:08:18**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **1000204886016, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **82 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST91000640SS

S/N: 9XG1KLVH

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE
product: ST91000640SS
revision: AS0D
compliance: SPC-4
user capacity: 1,000,204,886,016 bytes [1.00 TB]
logical block size: 512 bytes
rotation rate: 7200 rpm
form factor: 2.5 inches
logical unit id: 0x5000c500419cf5c7
serial number: 9XG1KLVH
device type: disk
transport protocol: SAS (SPL-3)
local time is: Sat Feb 15 20:43:57 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 37 C
drive trip temperature: 68 C

accumulated power on time, hours:minutes 21955:44
manufactured in week 16 of year 2012
specified cycle count over device lifetime: 10000
accumulated start-stop cycles: 22
specified load-unload count over device lifetime: 300000
accumulated load-unload cycles: 7251
elements in grown defect list: 1

vendor (seagate cache) information

blocks sent to initiator = 1435494267
blocks received from initiator = 2485540330
blocks read from cache and sent to initiator = 2373574830
number of read and write commands whose size <= segment size = 156121972
number of read and write commands whose size > segment size = 3

vendor (seagate/hitachi) factory information

number of hours powered up = 21955.73
number of minutes until next internal smart test = 59

error counter log:


| | errors corrected by | | | total | correction | | gigabytes | total |
|---------|---------------------|----------|-----------|-------------|------------|--------------|-----------|-------------|
| | ecc | rereads/ | | errors | algorithm | | processed | uncorrected |
| | fast delayed | rewrites | corrected | invocations | | [10^9 bytes] | errors | |
| read: | 1896722435 | 0 | 0 | 1896722435 | 0 | 0 | 32706.828 | 0 |
| write: | 0 | 0 | 0 | 0 | 0 | 23270.105 | 0 | 0 |
| verify: | 3252872563 | 0 | 0 | 3252872563 | 0 | 1013.494 | 0 | 0 |

non-medium error count: 576

smart self-test log

| num | test | status | segment | lifetime | lba_first_err | [sk asc asq] |
|-----|------------------|-----------|---------|----------|---------------|--------------|
| | description | | number | (hours) | | |
| # 1 | background short | completed | 32 | 65535 | - [- - -] | |
| # 2 | background short | completed | 32 | 65535 | - [- - -] | |

long (extended) self-test duration: 12198 seconds [203.3 minutes]



Model: SEAGATE ST91000640SS

S/N: 9XG1KLVH

Disk Erasure Report

Page 3 - Smart Data

