



Model: SEAGATE ST32000645SS  
S/N: 9XH045RX



# Disk Erasure Report

Page 1 - Erasure Status

## Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-3**

Contact Phone:

## Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

## Disk Information

Make/Model: **SEAGATE ST32000645SS**

Serial: **9XH045RX**

Size(Apparent): **2000 GB, 2000398934016 bytes**

Bus: **SAS**

Size(Real): **2000 GB, 2000398934016 bytes**

## Disk Erasure Details

Start time: **2025/02/15 10:41:05**

End time: **2025/02/16 01:51:37**

Duration: **15:10:32**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

\*Bytes Erased: **2000398934016, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **109 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

\* bytes erased: The amount of drive that's been erased at least once

## Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST32000645SS

S/N: 9XH045RX

# Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86\_64-linux-5.14.0-503.23.1.el9\_5.x86\_64] (local build)  
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE  
product: ST32000645SS  
revision: RS11  
compliance: SPC-4  
user capacity: 2,000,398,934,016 bytes [2.00 TB]  
logical block size: 512 bytes  
rotation rate: 7200 rpm  
form factor: 3.5 inches  
logical unit id: 0x5000c500427c841f  
serial number: 9XH045RX  
device type: disk  
transport protocol: SAS (SPL-3)  
local time is: Sun Feb 16 01:51:38 2025 GMT  
smart support is: Available - device has SMART capability.  
smart support is: Enabled  
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 32 C  
drive trip temperature: 68 C

accumulated power on time, hours:minutes 12081:56  
manufactured in week 39 of year 2012  
specified cycle count over device lifetime: 10000  
accumulated start-stop cycles: 3  
specified load-unload count over device lifetime: 300000  
accumulated load-unload cycles: 7590  
elements in grown defect list: 2

vendor (seagate cache) information

blocks sent to initiator = 965860777  
blocks received from initiator = 3367795574  
blocks read from cache and sent to initiator = 759811254  
number of read and write commands whose size <= segment size = 149609762  
number of read and write commands whose size > segment size = 0

vendor (seagate/hitachi) factory information

number of hours powered up = 12081.93  
number of minutes until next internal smart test = 59

error counter log:

	errors corrected by ecc	rereads/ rewrites	total errors corrected	correction algorithm invocations	gigabytes processed [10 <sup>9</sup> bytes]	total uncorrected errors
read:	3085770005	0	3085770005	0	9575.935	0
write:	0	0	0	1	131806.635	1
verify:	1038286254	0	1038286254	0	871206.493	0

non-medium error count: 173119

smart self-test log

num	test description	status	segment number	lifetime (hours)	lba_first_err [sk asc asq]
# 1	background long	completed	32	4	- [- - -]
# 2	reserved(7)	completed	16	2	- [- - -]
# 3	background short	completed	32	0	- [- - -]

long (extended) self-test duration: 32767 seconds [546.1 minutes]



Model: SEAGATE ST32000645SS  
S/N: 9XH045RX

# Disk Erasure Report

Page 3 - Smart Data

