

Model: SEAGATE ST9146853SS
S/N: 6XM46YAM



Disk Erasure Report

Page 1 - Erasure Status

Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-4**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE ST9146853SS**

Serial: **6XM46YAM**

Size(Apparent): **146 GB, 146815733760 bytes**

Bus: **SAS**

Size(Real): **146 GB, 146815733760 bytes**

Disk Erasure Details

Start time: **2025/02/16 02:02:01**

End time: **2025/02/16 02:49:28**

Duration: **00:47:27**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **146815733760, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **154 MB/sec**


Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST9146853SS
S/N: 6XM46YAM



Disk Erasure Report

Page 2 - Smart Data

smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE
product: ST9146853SS
revision: YS0C
compliance: SPC-4
user capacity: 146,815,733,760 bytes [146 GB]
logical block size: 512 bytes
rotation rate: 15000 rpm
form factor: 2.5 inches
logical unit id: 0x5000c5007de5301b
serial number: 6XM46YAM
device type: disk
transport protocol: SAS (SPL-3)
local time is: Sun Feb 16 02:49:31 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 32 C
drive trip temperature: 68 C

accumulated power on time, hours:minutes 63752:08
manufactured in week 38 of year 2014
specified cycle count over device lifetime: 10000
accumulated start-stop cycles: 29
elements in grown defect list: 0

vendor (seagate cache) information

blocks sent to initiator = 1067130979
blocks received from initiator = 1248674047
blocks read from cache and sent to initiator = 1098599214
number of read and write commands whose size <= segment size = 471116204
number of read and write commands whose size > segment size = 216

vendor (seagate/hitachi) factory information

number of hours powered up = 63752.13
number of minutes until next internal smart test = 11

error counter log:

| | errors corrected by | | | total | correction | gigabytes | total |
|---------|---------------------|----------|----------|-----------|-------------|--------------|-------------|
| | ecc | rereads/ | | errors | algorithm | processed | uncorrected |
| | fast | delayed | rewrites | corrected | invocations | [10^9 bytes] | errors |
| read: | 798048526 | 0 | 0 | 798048526 | 0 | 24214.255 | 0 |
| write: | 0 | 0 | 0 | 0 | 0 | 55817.095 | 0 |
| verify: | 245338905 | 0 | 0 | 245338905 | 0 | 50342.993 | 0 |

non-medium error count: 12

smart self-test log

| num | test | status | segment | lifetime | lba_first_err | [sk asc asq] |
|-----|------------------|-----------|---------|----------|---------------|--------------|
| | description | | number | (hours) | | |
| # 1 | background short | completed | 32 | 3 | - | [- - -] |
| # 2 | reserved(7) | completed | 32 | 3 | - | [- - -] |
| # 3 | background short | completed | 32 | 1 | - | [- - -] |

long (extended) self-test duration: 1099 seconds [18.3 minutes]