



Model: SEAGATE ST300MM0006

S/N: S0K3KKYY

# Disk Erasure Report

Page 1 - Erasure Status



## Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-2**

Contact Phone:

## Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

## Disk Information

Make/Model: **SEAGATE ST300MM0006**

Serial: **S0K3KKYY**

Size(Apparent): **300 GB, 300000000000 bytes**

Bus: **SAS**

Size(Real): **300 GB, 300000000000 bytes**

## Disk Erasure Details

Start time: **2025/02/16 01:52:33**

End time: **2025/02/16 03:21:20**

Duration: **01:28:47**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

\*Bytes Erased: **300000000000, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **168 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

\* bytes erased: The amount of drive that's been erased at least once

## Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST300MM0006

S/N: S0K3KKYY

# Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86\_64-linux-5.14.0-503.23.1.el9\_5.x86\_64] (local build)  
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE  
product: ST300MM0006  
revision: LS0C  
compliance: SPC-4  
user capacity: 300,000,000,000 bytes [300 GB]  
logical block size: 512 bytes  
lu is fully provisioned  
rotation rate: 10000 rpm  
form factor: 2.5 inches  
logical unit id: 0x5000c5007ed3c36f  
serial number: S0K3KKYY  
device type: disk  
transport protocol: SAS (SPL-3)  
local time is: Sun Feb 16 03:21:21 2025 GMT  
smart support is: Available - device has SMART capability.  
smart support is: Enabled  
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 31 C  
drive trip temperature: 60 C

accumulated power on time, hours:minutes 75460:47  
manufactured in week 48 of year 2014  
specified cycle count over device lifetime: 10000  
accumulated start-stop cycles: 144  
specified load-unload count over device lifetime: 300000  
accumulated load-unload cycles: 3261  
elements in grown defect list: 0

vendor (seagate cache) information

blocks sent to initiator = 3314944405  
blocks received from initiator = 3606707065  
blocks read from cache and sent to initiator = 3064781023  
number of read and write commands whose size <= segment size = 1451510118  
number of read and write commands whose size > segment size = 223

vendor (seagate/hitachi) factory information

number of hours powered up = 75460.78  
number of minutes until next internal smart test = 37

error counter log:

	errors corrected by		total	correction	gigabytes	total	
	ecc	rereads/	errors	algorithm	processed	uncorrected	
	fast   delayed	rewrites	corrected	invocations	[10^9 bytes]	errors	
read:	2242839021	0	0	2242839021	0	361284.110	0
write:	0	0	11	11	11	70523.196	0
verify:	781507968	0	0	781507968	0	127294.930	0

non-medium error count: 27

smart self-test log

num	test	status	segment	lifetime	lba_first_err	[sk asc asq]
	description		number	(hours)		
# 1	background short	completed	64	2	- [- - -]	
# 2	reserved(7)	completed	48	2	- [- - -]	
# 3	background short	completed	64	1	- [- - -]	



Model: SEAGATE ST300MM0006  
S/N: S0K3KKYY

# Disk Erasure Report

Page 3 - Smart Data



---

long (extended) self-test duration: 1905 seconds [31.8 minutes]