



Model: WD WD2000FYYG

S/N: WMAWP0287196

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-4**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **WD WD2000FYYG**

Serial: **WMAWP0287196**

Size(Apparent): **2000 GB, 2000398934016 bytes**

Bus: **SAS**

Size(Real): **2000 GB, 2000398934016 bytes**

Disk Erasure Details

Start time: **2025/02/15 10:42:24**

End time: **2025/02/16 04:22:02**

Duration: **17:39:38**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **2000398934016, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **94 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: WD WD2000FYYG

S/N: WMAWP0287196

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: WD
product: WD2000FYYG
revision: D1B3
compliance: SPC-4
user capacity: 2,000,398,934,016 bytes [2.00 TB]
logical block size: 512 bytes
rotation rate: 7200 rpm
form factor: 3.5 inches
logical unit id: 0x50014ee355667fa4
serial number: WMAWP0287196
device type: disk
transport protocol: SAS (SPL-3)
local time is: Sun Feb 16 04:22:04 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 35 C
drive trip temperature: 64 C

accumulated power on time, hours:minutes 70955:13
manufactured in week of year 2010
specified cycle count over device lifetime: 1048576
accumulated start-stop cycles: 3
specified load-unload count over device lifetime: 1114112
accumulated load-unload cycles: 3
elements in grown defect list: 0

error counter log:

	errors corrected by	total	correction	gigabytes	total
	ecc	errors	algorithm	processed	uncorrected
	fast delayed	rewrites	corrected	invocations	errors
read:	1010567 274	0	1010841	944	0.518 0
write:	955 28295584	0	28296539	28295584	1.603 0
verify:	15207 468	0	15675	540	0.008 0

non-medium error count: 3105153

smart self-test log

num	test	status	segment	lifetime	lba_first_err	[sk asc asq]
	description		number	(hours)		
# 1	background long	completed	32	7	- [- - -]	
# 2	background short	aborted (by user command)	32	2	- [- - -]	
# 3	background short	completed	32	0	- [- - -]	

long (extended) self-test duration: 64583 seconds [1076.4 minutes]