



Model: WD WD2000FYYG

S/N: WMAWP0275377

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-3**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **WD WD2000FYYG**

Serial: **WMAWP0275377**

Size(Apparent): **2000 GB, 2000398934016 bytes**

Bus: **SAS**

Size(Real): **2000 GB, 2000398934016 bytes**

Disk Erasure Details

Start time: **2025/02/15 10:40:52**

End time: **2025/02/16 04:32:49**

Duration: **17:51:57**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **2000398934016, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **93 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: WD WD2000FYYG

S/N: WMAWP0275377



Disk Erasure Report

Page 2 - Smart Data

smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: WD
product: WD2000FYYG
revision: D1B3
compliance: SPC-4
user capacity: 2,000,398,934,016 bytes [2.00 TB]
logical block size: 512 bytes
rotation rate: 7200 rpm
form factor: 3.5 inches
logical unit id: 0x50014ee300112a84
serial number: WMAWP0275377
device type: disk
transport protocol: SAS (SPL-3)
local time is: Sun Feb 16 04:32:51 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 36 C
drive trip temperature: 64 C

accumulated power on time, hours:minutes 109040:43
manufactured in week of year 2010
specified cycle count over device lifetime: 1048576
accumulated start-stop cycles: 4
specified load-unload count over device lifetime: 1114112
accumulated load-unload cycles: 4
elements in grown defect list: 0

error counter log:

	errors corrected by ecc	total errors	correction algorithm	gigabytes processed [10 ⁹ bytes]	total uncorrected errors
read:	fast delayed	rereads/ rewrites	corrected	invocations	
read:	1254980 1445	0	1256425	2372	0.644 0
write:	1040 29533840	0	29534880	29533840	2.237 0
verify:	53232 544	0	53776	544	0.028 0

non-medium error count: 2376101

smart self-test log

num	test description	status	segment number	lifetime (hours)	lba_first_err	[sk asc asq]
# 1	background long	completed	32	8	-	[- - -]
# 2	background short	aborted (by user command)	32	2	-	[- - -]
# 3	background short	completed	32	0	-	[- - -]

long (extended) self-test duration: 64583 seconds [1076.4 minutes]