



Model: MTFDDAK512TDL

S/N: 2006267635EA



Disk Erasure Report

Page 1 - Erasure Status

Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-3**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **MTFDDAK512TDL**

Serial: **2006267635EA**

Size(Apparent): **512 GB, 512110190592 bytes**

Bus: **ATA-SSD**

Size(Real): **512 GB, 512110190592 bytes**

Disk Erasure Details

Start time: **2025/02/16 10:46:12**

End time: **2025/02/16 12:07:00**

Duration: **01:20:48**

Status: **ERASED**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **512110190592, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **No hidden sectors**

HPA/DCO Size: **No hidden sectors**

Errors(pass/sync/verify): **0/0/0**

Throughput: **316 MB/sec**

Information:

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: MTFDDAK512TDL

S/N: 2006267635EA

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

model family: Crucial/Micron Client SSDs
device model: MTFDDAK512TDL
serial number: 2006267635EA
lu wwn device id: 5 00a075 1267635ea
firmware version: M5MU030
user capacity: 512,110,190,592 bytes [512 GB]
sector size: 512 bytes logical/physical
rotation rate: Solid State Device
form factor: 2.5 inches
trim command: Available, deterministic, zeroed
device is: In smartctl database [for details use: -P show]
ata version is: ACS-4 T13/BSR INCITS 529 revision 5
sata version is: SATA 3.3, 6.0 Gb/s (current: 6.0 Gb/s)
local time is: Sun Feb 16 12:07:05 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled

=== start of read smart data section ===

smart overall-health self-assessment test result: PASSED


general smart values:

offline data collection status: (0x00)Offline data collection activity
was never started.
auto offline data collection: Disabled.
self-test execution status: (0)The previous self-test routine completed
without error or no self-test has ever
been run.
total time to complete offline
data collection: (1357) seconds.
offline data collection
capabilities: (0x7b) SMART execute Offline immediate.
auto offline data collection on/off support.
suspend offline collection upon new
command.
offline surface scan supported.
self-test supported.
conveyance self-test supported.
selective self-test supported.
smart capabilities: (0x0003)Saves SMART data before entering
power-saving mode.
supports smart auto save timer.
error logging capability: (0x01)Error logging supported.
general purpose logging supported.
short self-test routine
recommended polling time: (2) minutes.
extended self-test routine
recommended polling time: (7) minutes.
conveyance self-test routine
recommended polling time: (3) minutes.
sct capabilities: (0x0035)SCT Status supported.
sct feature control supported.
sct data table supported.

smart attributes data structure revision number: 16

vendor specific smart attributes with thresholds:

id#	attribute_name	flag	value	worst	thresh	type	updated	when_failed	raw_value
1	raw_read_error_rate	0x002f	100	100	000	pre-fail	always	-	0
5	reallocate_nand_blk_cnt	0x0032	100	100	010	old_age	always	-	0
9	power_on_hours	0x0032	100	100	000	old_age	always	-	14484
12	power_cycle_count	0x0032	100	100	000	old_age	always	-	24



Model: MTFDDAK512TDL

S/N: 2006267635EA



Disk Erasure Report

Page 3 - Smart Data

171	program_fail_count	0x0032	100	100	000	old_age	always	-	0
172	erase_fail_count	0x0032	100	100	000	old_age	always	-	0
173	ave_block-erase_count	0x0032	098	098	000	old_age	always	-	48
174	unexpect_power_loss_ct	0x0032	100	100	000	old_age	always	-	20
183	sata_interfac_downshift	0x0032	100	100	000	old_age	always	-	0
184	error_correction_count	0x0032	100	100	000	old_age	always	-	0
187	reported_uncorrect	0x0032	100	100	000	old_age	always	-	0
194	temperature_celsius	0x0022	059	058	000	old_age	always	-	41 (min/max 6/42)
196	reallocated_event_count	0x0032	100	100	000	old_age	always	-	0
197	current_pending_ecc_cnt	0x0032	100	100	000	old_age	always	-	0
198	offline_uncorrectable	0x0030	100	100	000	old_age	offline	-	0
199	udma_crc_error_count	0x0032	100	100	000	old_age	always	-	0
202	percent_lifetime_remain	0x0030	098	098	001	old_age	offline	-	2
206	write_error_rate	0x000e	100	100	000	old_age	always	-	0
246	total_lbas_written	0x0032	100	100	000	old_age	always	-	26953486194
247	host_program_page_count	0x0032	100	100	000	old_age	always	-	842296549
248	ftl_program_page_count	0x0032	100	100	000	old_age	always	-	270643022
180	unused_reserve_nand_blk	0x0033	000	000	000	pre-fail	always	-	852
210	success_rain_recov_cnt	0x0032	100	100	000	old_age	always	-	0

smart error log version: 1
no errors logged

smart self-test log structure revision number 1

num	test_description	status	remaining	lifetime(hours)	lba_of_first_error
# 1	vendor (0xff)	completed without error	00%	14478	-
# 2	vendor (0xff)	completed without error	00%	14336	-
# 3	vendor (0xff)	completed without error	00%	13920	-
# 4	vendor (0xff)	completed without error	00%	13517	-
# 5	vendor (0xff)	completed without error	00%	13117	-
# 6	vendor (0xff)	completed without error	00%	12688	-
# 7	vendor (0xff)	completed without error	00%	12511	-
# 8	vendor (0xff)	completed without error	00%	12170	-
# 9	vendor (0xff)	completed without error	00%	11808	-
#10	vendor (0xff)	completed without error	00%	11470	-
#11	vendor (0xff)	completed without error	00%	11119	-
#12	vendor (0xff)	completed without error	00%	10667	-
#13	vendor (0xff)	completed without error	00%	10461	-
#14	vendor (0xff)	completed without error	00%	10168	-
#15	vendor (0xff)	completed without error	00%	9801	-
#16	vendor (0xff)	completed without error	00%	9585	-
#17	vendor (0xff)	completed without error	00%	9282	-
#18	vendor (0xff)	completed without error	00%	8914	-
#19	vendor (0xff)	completed without error	00%	8582	-
#20	vendor (0xff)	completed without error	00%	8206	-
#21	vendor (0xff)	completed without error	00%	7828	-

smart selective self-test log data structure revision number 1

span	min_lba	max_lba	current_test_status
1	0	0	not_testing
2	0	0	not_testing
3	0	0	not_testing
4	0	0	not_testing
5	0	0	not_testing

selective self-test flags (0x0):

after scanning selected spans, do not read-scan remainder of disk.
if selective self-test is pending on power-up, resume after 0 minute delay.