



Model: WD WD2000FYYG

S/N: WMAWP0278563

# Disk Erasure Report

Page 1 - Erasure Status



## Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-3**

Contact Phone:

## Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

## Disk Information

Make/Model: **WD WD2000FYYG**

Serial: **WMAWP0278563**

Size(Apparent): **2000 GB, 2000398934016 bytes**

Bus: **SAS**

Size(Real): **2000 GB, 2000398934016 bytes**

## Disk Erasure Details

Start time: **2025/02/15 10:40:25**

End time: **2025/02/16 15:31:39**

Duration: **28:51:14**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

\*Bytes Erased: **2000398934016, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **57 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

\* bytes erased: The amount of drive that's been erased at least once

## Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: WD WD2000FYYG

S/N: WMAWP0278563



# Disk Erasure Report

Page 2 - Smart Data

smartctl 7.2 2020-12-30 r5155 [x86\_64-linux-5.14.0-503.23.1.el9\_5.x86\_64] (local build)  
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: WD  
product: WD2000FYYG  
revision: D1B3  
compliance: SPC-4  
user capacity: 2,000,398,934,016 bytes [2.00 TB]  
logical block size: 512 bytes  
rotation rate: 7200 rpm  
form factor: 3.5 inches  
logical unit id: 0x50014ee30010e310  
serial number: WMAWP0278563  
device type: disk  
transport protocol: SAS (SPL-3)  
local time is: Sun Feb 16 15:31:40 2025 GMT  
smart support is: Available - device has SMART capability.  
smart support is: Enabled  
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 36 C  
drive trip temperature: 64 C

accumulated power on time, hours:minutes 109051:43  
manufactured in week of year 2010  
specified cycle count over device lifetime: 1048576  
accumulated start-stop cycles: 4  
specified load-unload count over device lifetime: 1114112  
accumulated load-unload cycles: 4  
elements in grown defect list: 0

error counter log:

|         | errors corrected by | total    | correction | gigabytes   | total       |
|---------|---------------------|----------|------------|-------------|-------------|
|         | ecc                 | errors   | algorithm  | processed   | uncorrected |
|         | fast   delayed      | rewrites | corrected  | invocations | errors      |
| read:   | 1238586 504         | 0        | 1239090    | 1508        | 0.635       |
| write:  | 847 29847349        | 0        | 29848196   | 29847349    | 2.397       |
| verify: | 17762 130           | 0        | 17892      | 130         | 0.009       |

non-medium error count: 5127617

smart self-test log

| num | test             | status                    | segment | lifetime | lba_first_err | [sk asc asq] |
|-----|------------------|---------------------------|---------|----------|---------------|--------------|
|     | description      |                           | number  | (hours)  |               |              |
| # 1 | background long  | completed                 | 32      | 8        | -             | [- - -]      |
| # 2 | background short | aborted (by user command) | 32      | 2        | -             | [- - -]      |
| # 3 | background short | aborted (device reset ?)  | 32      | 0        | -             | [- - -]      |

long (extended) self-test duration: 64583 seconds [1076.4 minutes]