



Model: SEAGATE ST973401SS

S/N: 3LB0P4HX

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-0**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE ST973401SS**

Serial: **3LB0P4HX**

Size(Apparent): **73 GB, 73407820800 bytes**

Bus: **SAS**

Size(Real): **73 GB, 73407820800 bytes**

Disk Erasure Details

Start time: **2025/02/16 17:17:32**

End time: **2025/02/16 18:34:04**

Duration: **01:16:32**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **73407820800, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **47 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST973401SS

S/N: 3LB0P4HX

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.22.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE
product: ST973401SS
revision: S108
compliance: SPC-3
user capacity: 73,407,820,800 bytes [73.4 GB]
logical block size: 512 bytes
rotation rate: 10033 rpm
logical unit id: 0x5000c50000d09f2b
serial number: 3LB0P4HX
device type: disk
transport protocol: SAS (SPL-3)
local time is: Sun Feb 16 18:34:06 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 33 C
drive trip temperature: 68 C

accumulated power on time, hours:minutes 155896:52
elements in grown defect list: 0

vendor (seagate cache) information

blocks sent to initiator = 151249397
blocks received from initiator = 2547967122
blocks read from cache and sent to initiator = 3641958405
number of read and write commands whose size <= segment size = 3217863818
number of read and write commands whose size > segment size = 21639

vendor (seagate/hitachi) factory information

number of hours powered up = 155921.38
number of minutes until next internal smart test = 120

error counter log:

	errors corrected by ecc	rereads/ rewrites	total errors corrected	correction algorithm invocations	gigabytes processed [10 ⁹ bytes]	total uncorrected errors
read:	26600328	0	26600328	26600328	50788.546	0
write:	0	0	0	0	28986.392	0
verify:	498252	0	498252	498252	47641.158	0

non-medium error count: 15

smart self-test log

num	test	status	segment number	lifetime (hours)	lba_first_err	[sk asc asq]
# 1	background long	completed	-	1	-	[- - -]
# 2	background short	completed	-	1	-	[- - -]

long (extended) self-test duration: 1560 seconds [26.0 minutes]