



Model: SEAGATE ST600MM0088

S/N: S4103JA8

# Disk Erasure Report

Page 1 - Erasure Status



## Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-0**

Contact Phone:

## Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

## Disk Information

Make/Model: **SEAGATE ST600MM0088**

Serial: **S4103JA8**

Size(Apparent): **600 GB, 600127266816 bytes**

Bus: **SAS**

Size(Real): **600 GB, 600127266816 bytes**

## Disk Erasure Details

Start time: **2025/02/16 17:17:47**

End time: **2025/02/16 20:41:40**

Duration: **03:23:53**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

\*Bytes Erased: **600127266816, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **147 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

\* bytes erased: The amount of drive that's been erased at least once

## Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST600MM0088

S/N: S4103JA8

# Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86\_64-linux-5.14.0-503.22.1.el9\_5.x86\_64] (local build)  
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE  
product: ST600MM0088  
revision: TS03  
compliance: SPC-4  
user capacity: 600,127,266,816 bytes [600 GB]  
logical block size: 512 bytes  
lu is fully provisioned  
rotation rate: 10000 rpm  
form factor: 2.5 inches  
logical unit id: 0x5000c50088e98907  
serial number: S4103JA8  
device type: disk  
transport protocol: SAS (SPL-3)  
local time is: Sun Feb 16 20:41:42 2025 GMT  
smart support is: Available - device has SMART capability.  
smart support is: Enabled  
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

grown defects during certification <not available>  
total blocks reassigned during format <not available>  
total new blocks reassigned <not available>  
power on minutes since format <not available>  
current drive temperature: 30 C  
drive trip temperature: 60 C

accumulated power on time, hours:minutes 70610:19  
manufactured in week 15 of year 2015  
specified cycle count over device lifetime: 10000  
accumulated start-stop cycles: 12  
specified load-unload count over device lifetime: 300000  
accumulated load-unload cycles: 2953  
elements in grown defect list: 1

vendor (seagate cache) information

blocks sent to initiator = 4292335476  
blocks received from initiator = 3340220864  
blocks read from cache and sent to initiator = 1121002993  
number of read and write commands whose size <= segment size = 962247690  
number of read and write commands whose size > segment size = 0

vendor (seagate/hitachi) factory information

number of hours powered up = 70610.32  
number of minutes until next internal smart test = 42

error counter log:

	errors corrected by ecc	fast   delayed	rereads/ rewrites	total errors corrected	correction algorithm invocations	gigabytes processed [10^9 bytes]	total uncorrected errors
read:	2283309618	0	0	2283309618	0	180673.184	0
write:	0	0	160	160	161	50267.937	0
verify:	1986551249	0	0	1986551249	0	252533.050	0

non-medium error count: 686

no self-tests have been logged