



Model: SEAGATE ST600MM0006

S/N: S0M3LMGA

# Disk Erasure Report

Page 1 - Erasure Status



## Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-6**

Contact Phone:

## Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

## Disk Information

Make/Model: **SEAGATE ST600MM0006**

Serial: **S0M3LMGA**

Size(Apparent): **600 GB, 600127266816 bytes**

Bus: **SAS**

Size(Real): **600 GB, 600127266816 bytes**

## Disk Erasure Details

Start time: **2025/02/16 17:20:45**

End time: **2025/02/16 20:49:22**

Duration: **03:28:37**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

\*Bytes Erased: **600127266816, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **143 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

\* bytes erased: The amount of drive that's been erased at least once

## Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST600MM0006

S/N: S0M3LMGA

# Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86\_64-linux-5.14.0-503.23.1.el9\_5.x86\_64] (local build)  
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE  
product: ST600MM0006  
revision: LS0A  
compliance: SPC-4  
user capacity: 600,127,266,816 bytes [600 GB]  
logical block size: 512 bytes  
lu is fully provisioned  
rotation rate: 10000 rpm  
form factor: 2.5 inches  
logical unit id: 0x5000c5007de71513  
serial number: S0M3LMGA  
device type: disk  
transport protocol: SAS (SPL-3)  
local time is: Sun Feb 16 20:49:23 2025 GMT  
smart support is: Available - device has SMART capability.  
smart support is: Enabled  
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 30 C  
drive trip temperature: 50 C

accumulated power on time, hours:minutes 5925:24  
manufactured in week 38 of year 2014  
specified cycle count over device lifetime: 10000  
accumulated start-stop cycles: 144  
specified load-unload count over device lifetime: 300000  
accumulated load-unload cycles: 4870  
elements in grown defect list: 0

vendor (seagate cache) information

blocks sent to initiator = 2173464636  
blocks received from initiator = 83432575  
blocks read from cache and sent to initiator = 3910412611  
number of read and write commands whose size <= segment size = 1825136805  
number of read and write commands whose size > segment size = 0

vendor (seagate/hitachi) factory information

number of hours powered up = 5925.40  
number of minutes until next internal smart test = 40

error counter log:

	errors corrected by		total	correction	gigabytes	total	
	ecc	rereads/	errors	algorithm	processed	uncorrected	
	fast   delayed	rewrites	corrected	invocations	[10^9 bytes]	errors	
read:	2205896415	0	0	2205896415	0	544550.039	0
write:	0	0	15	15	135505.399	0	0
verify:	3713045753	0	0	3713045753	0	287986.839	0

non-medium error count: 79

no self-tests have been logged