



Model: SEAGATE ST600MM0006

S/N: S0M3N3F0

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-6**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE ST600MM0006**

Serial: **S0M3N3F0**

Size(Apparent): **600 GB, 600127266816 bytes**

Bus: **SAS**

Size(Real): **600 GB, 600127266816 bytes**

Disk Erasure Details

Start time: **2025/02/16 17:20:47**

End time: **2025/02/16 20:54:09**

Duration: **03:33:22**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **600127266816, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **140 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST600MM0006

S/N: S0M3N3F0

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE
product: ST600MM0006
revision: LS0A
compliance: SPC-4
user capacity: 600,127,266,816 bytes [600 GB]
logical block size: 512 bytes
lu is fully provisioned
rotation rate: 10000 rpm
form factor: 2.5 inches
logical unit id: 0x5000c5007de658a3
serial number: S0M3N3F0
device type: disk
transport protocol: SAS (SPL-3)
local time is: Sun Feb 16 20:54:11 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 30 C
drive trip temperature: 50 C

accumulated power on time, hours:minutes 5925:16
manufactured in week 38 of year 2014
specified cycle count over device lifetime: 10000
accumulated start-stop cycles: 144
specified load-unload count over device lifetime: 300000
accumulated load-unload cycles: 5849
elements in grown defect list: 0

vendor (seagate cache) information

blocks sent to initiator = 661754198
blocks received from initiator = 717462685
blocks read from cache and sent to initiator = 3009500015
number of read and write commands whose size <= segment size = 1808177334
number of read and write commands whose size > segment size = 0

vendor (seagate/hitachi) factory information

number of hours powered up = 5925.27
number of minutes until next internal smart test = 35

error counter log:

	errors corrected by ecc	fast delayed	rereads/ rewrites	total errors corrected	correction algorithm invocations	gigabytes processed [10 ⁹ bytes]	total uncorrected errors
read:	820714110	0	0	820714110	0	530526.354	0
write:	0	0	13	13	13	138592.921	0
verify:	1291994286	0	0	1291994286	0	288175.533	0

non-medium error count: 52

no self-tests have been logged