



Model: HITACHI HUC106060CSS600

S/N: PVHG6HYB

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-6**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **HITACHI HUC106060CSS600**

Serial: **PVHG6HYB**

Size(Apparent): **600 GB, 600127266816 bytes**

Bus: **SAS**

Size(Real): **600 GB, 600127266816 bytes**

Disk Erasure Details

Start time: **2025/02/16 17:20:09**

End time: **2025/02/16 21:24:36**

Duration: **04:04:27**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **600127266816, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **122 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: HITACHI HUC106060CSS600

S/N: PVHG6HYB

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: HITACHI
product: HUC106060CSS600
revision: A360
compliance: SPC-4
user capacity: 600,127,266,816 bytes [600 GB]
logical block size: 512 bytes
rotation rate: 10000 rpm
form factor: 2.5 inches
logical unit id: 0x5000cca02552349c
serial number: PVHG6HYB
device type: disk
transport protocol: SAS (SPL-3)
local time is: Sun Feb 16 21:24:38 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 31 C
drive trip temperature: 85 C

accumulated power on time, hours:minutes 15617:02
manufactured in week 11 of year 2012
specified cycle count over device lifetime: 50000
accumulated start-stop cycles: 31
specified load-unload count over device lifetime: 600000
accumulated load-unload cycles: 3161
elements in grown defect list: 0

vendor (seagate cache) information
blocks sent to initiator = 50332196380082176

error counter log:

	errors corrected by			total	correction	gigabytes	total
	ecc		rereads/	errors	algorithm	processed	uncorrected
	fast	delayed	rewrites	corrected	invocations	[10 ⁹ bytes]	errors
read:	525726905	1169010	0	526895915	6046944	32979.879	0
write:	0	389650	0	389650	392643	76844.254	0
verify:	2342680950	23313	0	2342704263	50585	121231.709	0

non-medium error count: 1

smart self-test log

num	test	status	segment	lifetime	lba_first_err	[sk asc asq]
	description		number	(hours)		
# 1	background long	completed	32	2	-	[- - -]
# 2	background short	completed	32	1	-	[- - -]

long (extended) self-test duration: 4889 seconds [81.5 minutes]