



Model: HITACHI HUC106060CSS600

S/N: PZHW97PD

# Disk Erasure Report

Page 1 - Erasure Status



## Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-6**

Contact Phone:

## Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

## Disk Information

Make/Model: **HITACHI HUC106060CSS600**

Serial: **PZHW97PD**

Size(Apparent): **600 GB, 600127266816 bytes**

Bus: **SAS**

Size(Real): **600 GB, 600127266816 bytes**

## Disk Erasure Details

Start time: **2025/02/16 17:21:54**

End time: **2025/02/16 21:26:06**

Duration: **04:04:12**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

\*Bytes Erased: **600127266816, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **122 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

\* bytes erased: The amount of drive that's been erased at least once

## Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: HITACHI HUC106060CSS600

S/N: PZHW97PD

# Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86\_64-linux-5.14.0-503.23.1.el9\_5.x86\_64] (local build)  
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: HITACHI  
product: HUC106060CSS600  
revision: A360  
compliance: SPC-4  
user capacity: 600,127,266,816 bytes [600 GB]  
logical block size: 512 bytes  
rotation rate: 10000 rpm  
form factor: 2.5 inches  
logical unit id: 0x5000cca03c6a00f4  
serial number: PZHW97PD  
device type: disk  
transport protocol: SAS (SPL-3)  
local time is: Sun Feb 16 21:26:08 2025 GMT  
smart support is: Available - device has SMART capability.  
smart support is: Enabled  
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 35 C  
drive trip temperature: 85 C

accumulated power on time, hours:minutes 24428:46  
manufactured in week 50 of year 2012  
specified cycle count over device lifetime: 50000  
accumulated start-stop cycles: 44  
specified load-unload count over device lifetime: 600000  
accumulated load-unload cycles: 3541  
elements in grown defect list: 0

vendor (seagate cache) information

blocks sent to initiator = 61461377562181632

error counter log:

	errors corrected by ecc	rereads/ rewrites	total errors corrected	correction algorithm invocations	gigabytes processed [10 <sup>9</sup> bytes]	total uncorrected errors
read:	3327340505 3883293	0	3331223798	17395135	89697.420	0
write:	0 556872	0	556872	557858	165128.076	0
verify:	17386195906 31440	0	17386227346	192518	300065.649	0

non-medium error count: 0

smart self-test log

num	test description	status	segment number	lifetime (hours)	lba_first_err	[sk asc asq]
# 1	background short	completed	32	3	-	[- - -]
# 2	background long	completed	32	3	-	[- - -]
# 3	background short	completed	32	2	-	[- - -]

long (extended) self-test duration: 4889 seconds [81.5 minutes]