



Model: SEAGATE ST9600205SS  
S/N: 6XR2VY7E



# Disk Erasure Report

Page 1 - Erasure Status

## Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-0**

Contact Phone:

## Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

## Disk Information

Make/Model: **SEAGATE ST9600205SS**

Serial: **6XR2VY7E**

Size(Apparent): **600 GB, 600127266816 bytes**

Bus: **SAS**

Size(Real): **600 GB, 600127266816 bytes**

## Disk Erasure Details

Start time: **2025/02/16 17:17:22**

End time: **2025/02/16 21:32:45**

Duration: **04:15:23**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

\*Bytes Erased: **600127266816, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **117 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

\* bytes erased: The amount of drive that's been erased at least once

## Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST9600205SS  
S/N: 6XR2VY7E



# Disk Erasure Report

Page 2 - Smart Data

smartctl 7.2 2020-12-30 r5155 [x86\_64-linux-5.14.0-503.22.1.el9\_5.x86\_64] (local build)  
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE  
product: ST9600205SS  
revision: CS09  
compliance: SPC-4  
user capacity: 600,127,266,816 bytes [600 GB]  
logical block size: 512 bytes  
rotation rate: 10000 rpm  
form factor: 2.5 inches  
logical unit id: 0x5000c50054701edf  
serial number: 6XR2VY7E  
device type: disk  
transport protocol: SAS (SPL-3)  
local time is: Sun Feb 16 21:32:47 2025 GMT  
smart support is: Available - device has SMART capability.  
smart support is: Enabled  
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 31 C  
drive trip temperature: 68 C

accumulated power on time, hours:minutes 22023:54  
manufactured in week 24 of year 2012  
specified cycle count over device lifetime: 10000  
accumulated start-stop cycles: 12  
specified load-unload count over device lifetime: 300000  
accumulated load-unload cycles: 4102  
elements in grown defect list: 111

vendor (seagate cache) information

blocks sent to initiator = 375281284  
blocks received from initiator = 951174294  
blocks read from cache and sent to initiator = 333255869  
number of read and write commands whose size <= segment size = 71795775  
number of read and write commands whose size > segment size = 115

vendor (seagate/hitachi) factory information

number of hours powered up = 22023.90  
number of minutes until next internal smart test = 59

error counter log:

	errors corrected by			total	correction	gigabytes	total
	ecc	rereads/		errors	algorithm	processed	uncorrected
	fast	delayed	rewrites	corrected	invocations	[10^9 bytes]	errors
read:	554270592	9	0	554270601	60	885514.614	51
write:	0	0	1	1	3	378166.548	2
verify:	4156278777	153	0	4156278930	236	350038.974	8

non-medium error count: 3351

smart self-test log

num	test	status	segment	lifetime	lba_first_err	[sk asc asq]
	description		number	(hours)		
# 1	background long	completed	32	4	-	[- - -]
# 2	background short	completed	32	3	-	[- - -]

long (extended) self-test duration: 5040 seconds [84.0 minutes]



Model: SEAGATE ST9600205SS

S/N: 6XR2VY7E

# Disk Erasure Report

Page 3 - Smart Data

