



Model: SEAGATE ST9600204SS  
S/N: 3WN0ANAH



# Disk Erasure Report

Page 1 - Erasure Status

## Organisation Performing The Disk Erasure

Business Name: **Not Applicable (BN)**

Business Address: **Not Applicable (BA)**

Contact Name: **Not Applicable (BCN)**

Contact Phone: **Not Applicable (BCP)**

## Customer Details

Name: **Not Applicable (CN)**

Address: **Not Applicable (CA)**

Contact Name: **Not Applicable (CCN)**

Contact Phone: **Not Applicable (CP)**

## Disk Information

Make/Model: **SEAGATE ST9600204SS**

Serial: **3WN0ANAH**

Size(Apparent): **600 GB, 600127266816 bytes**

Bus: **SAS**

Size(Real): **600 GB, 600127266816 bytes**

## Disk Erasure Details

Start time: **2025/02/16 17:18:21**

End time: **2025/02/16 21:34:53**

Duration: **04:16:32**

Status: **FAILED**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

\*Bytes Erased: **600127266816, (100.00%)**

Rounds(completed/requested): **0/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **1/0/0**

Throughput: **78 MB/sec**

Information: **Warning** HPA/DCO data unavailable, can not determine hidden sector status.

\* bytes erased: The amount of drive that's been erased at least once

## Technician/Operator ID

Signature:

Name/ID: **Not Applicable (OTN)**



Model: SEAGATE ST9600204SS  
S/N: 3WN0ANAH



# Disk Erasure Report

Page 2 - Smart Data

smartctl 7.2 2020-12-30 r5155 [x86\_64-linux-5.14.0-503.23.1.el9\_5.x86\_64] (local build)  
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE  
product: ST9600204SS  
revision: FM0A  
compliance: SPC-3  
user capacity: 600,127,266,816 bytes [600 GB]  
logical block size: 512 bytes  
rotation rate: 10000 rpm  
form factor: 2.5 inches  
logical unit id: 0x5000c5002411c0b7  
serial number: 3WN0ANAH  
device type: disk  
transport protocol: SAS (SPL-3)  
local time is: Sun Feb 16 21:34:54 2025 GMT  
smart support is: Available - device has SMART capability.  
smart support is: Enabled  
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: HARDWARE IMPENDING FAILURE GENERAL HARD DRIVE FAILURE [asc=5d, ascq=10]

current drive temperature: 44 C  
drive trip temperature: 68 C

accumulated power on time, hours:minutes 38162:08  
manufactured in week 33 of year 2010  
specified cycle count over device lifetime: 10000  
accumulated start-stop cycles: 40  
specified load-unload count over device lifetime: 300000  
accumulated load-unload cycles: 40  
elements in grown defect list: 694

vendor (seagate cache) information

blocks sent to initiator = 3190975437  
blocks received from initiator = 2394825043  
blocks read from cache and sent to initiator = 793649805  
number of read and write commands whose size <= segment size = 1677307650  
number of read and write commands whose size > segment size = 0

vendor (seagate/hitachi) factory information

number of hours powered up = 38162.13  
number of minutes until next internal smart test = 59

error counter log:

	errors corrected by ecc	rereads/ rewrites	total errors corrected	correction algorithm invocations	gigabytes processed [10^9 bytes]	total uncorrected errors
read:	3562104883	194	0	3562105077	90226.315	2
write:	0	0	513	516	41240.376	0
verify:	2053693805	2465	0	2053696270	401192.650	22

non-medium error count: 1953

smart self-test log

num	test description	status	segment number	lifetime (hours)	lba_first_err [sk asc asq]
# 1	background long	completed	16	31	- [- - -]
# 2	background short	completed	16	29	- [- - -]
# 3	background long	completed	16	5	- [- - -]
# 4	background short	completed	16	4	- [- - -]



Model: SEAGATE ST9600204SS  
S/N: 3WN0ANAH

# Disk Erasure Report

Page 3 - Smart Data



---

long (extended) self-test duration: 6176 seconds [102.9 minutes]